

► 19" LCD DISPLAY

NeoV OPTICAL GLASS

E-19



► FEATURES







- Exceptionally elegant exterior
- Stylish rear side design
- Swift 4ms response time
- Crisp 700 contrast ratio
- NeoV Optical Glass[™]
- Dual digital and analog inputs
- Built-in speakers with headphone jack
- · Auto-adjustment for optimal setting
- Intuitive OSD with key lock function
- Kensington® security socket
- VESA standard wall mount









► SPECIFICATION

Panel	Panel Type	TFT LCD
	Panel Size	19.0" (483mm)
	Max. Resolution	SXGA 1280 x 1024
	Pixel Pitch	0.294mm
	Brightness	300cd/m ² (Typical)
	Contrast Ratio	700:1 (Typical)
	Surface Treatments	Hard Coating (2H), Anti-glare
		Treatment
	Viewing Angle (H/V)	150°/135° (Typical)
	Display Color	16.7M
	Response Time	4ms (GTG)
	Frequency (H/V)	H: 24kHz - 80kHz
		V: 56Hz - 75Hz
	Max. Pixel Clock	135MHz
	Life Time	50,000hrs (Typical)
Input	Analog	15-Pin D-Sub
	Digital	24-Pin DVI-D
Audio	Audio In	3.5mm Audio Line-in
	Audio Out	3.5mm Headphone Jack
	Speaker	1W x 2
Connector	Power	3-Pin AC Plug
NeoV Optical	Thickness	3.0mm (0.18")
Glass	Reflection Rate	<1%
	Transmission Rate	>96%
	Hardness	>6H (MOH's Rating)
Tilt	Tilt	+5° ~ +25°
Tilt Mounting	Tilt VESA FPMPMI	+5° ~ +25° Yes (100mm)
Mounting	VESA FPMPMI	Yes (100mm) UL/CUL, TUV/BAURT,
Mounting Regulation	VESA FPMPMI Certifications &	Yes (100mm) UL/CUL, TUV/BAURT,
Mounting Regulation	VESA FPMPMI Certifications &	Yes (100mm) UL/CUL, TUV/BAURT, NORDIC, CB, FCC, CE, BSMI,
Mounting Regulation Approval	VESA FPMPMI Certifications & Compliance	Yes (100mm) UL/CUL, TUV/BAURT, NORDIC, CB, FCC, CE, BSMI, EPA, GOST, WEEE, ROHS
Mounting Regulation Approval	VESA FPMPMI Certifications & Compliance VESA	Yes (100mm) UL/CUL, TUV/BAURT, NORDIC, CB, FCC, CE, BSMI, EPA, GOST, WEEE, RoHS DDC 2B, DPMS
Mounting Regulation	VESA FPMPMI Certifications & Compliance VESA Power AC	Yes (100mm) UL/CUL, TUV/BAURT, NORDIC, CB, FCC, CE, BSMI, EPA, GOST, WEEE, RoHS DDC 2B, DPMS 100 - 240V, 50 - 60Hz
Mounting Regulation Approval	VESA FPMPMI Certifications & Compliance VESA Power AC	Yes (100mm) UL/CUL, TUV/BAURT, NORDIC, CB, FCC, CE, BSMI, EPA, GOST, WEEE, RoHS DDC 2B, DPMS 100 - 240V, 50 - 60Hz <55W (On)
Mounting Regulation Approval	VESA FPMPMI Certifications & Compliance VESA Power AC	Yes (100mm) UL/CUL, TUV/BAURT, NORDIC, CB, FCC, CE, BSMI, EPA, GOST, WEEE, RoHS DDC 2B, DPMS 100 - 240V, 50 - 60Hz <55W (On) <2W (Stand-by)
Mounting Regulation Approval Power	VESA FPMPMI Certifications & Compliance VESA Power AC Consumption	Yes (100mm) UL/CUL, TUV/BAURT, NORDIC, CB, FCC, CE, BSMI, EPA, GOST, WEEE, ROHS DDC 2B, DPMS 100 - 240V, 50 - 60Hz <55W (On) <2W (Stand-by) <1W (Off)
Mounting Regulation Approval Power	VESA FPMPMI Certifications & Compliance VESA Power AC Consumption	Yes (100mm) UL/CUL, TUV/BAURT, NORDIC, CB, FCC, CE, BSMI, EPA, GOST, WEEE, ROHS DDC 2B, DPMS 100 - 240V, 50 - 60Hz <55W (On) <2W (Stand-by) <1W (Off) 437 x 450 x 196mm
Mounting Regulation Approval Power	VESA FPMPMI Certifications & Compliance VESA Power AC Consumption Net (W x H x D)	Yes (100mm) UL/CUL, TUV/BAURT, NORDIC, CB, FCC, CE, BSMI, EPA, GOST, WEEE, RoHS DDC 2B, DPMS 100 - 240V, 50 - 60Hz <55W (On) <2W (Stand-by) <1W (Off) 437 x 450 x 196mm (17.2" x 17.7" x 7.7")
Mounting Regulation Approval Power	VESA FPMPMI Certifications & Compliance VESA Power AC Consumption Net (W x H x D)	Yes (100mm) UL/CUL, TUV/BAURT, NORDIC, CB, FCC, CE, BSMI, EPA, GOST, WEEE, RoHS DDC 2B, DPMS 100 - 240V, 50 - 60Hz <55W (On) <2W (Stand-by) <1W (Off) 437 x 450 x 196mm (17.2" x 17.7" x 7.7") 555 x 580 x 171mm
Mounting Regulation Approval Power Dimensions	VESA FPMPMI Certifications & Compliance VESA Power AC Consumption Net (W x H x D) Packing (W x H x D)	Yes (100mm) UL/CUL, TUV/BAURT, NORDIC, CB, FCC, CE, BSMI, EPA, GOST, WEEE, ROHS DDC 2B, DPMS 100 - 240V, 50 - 60Hz <55W (On) <2W (Stand-by) <1W (Off) 437 x 450 x 196mm (17.2" x 17.7" x 7.7") 555 x 580 x 171mm (21.9" x 22.8" x 6.7")
Mounting Regulation Approval Power Dimensions	VESA FPMPMI Certifications & Compliance VESA Power AC Consumption Net (W x H x D) Packing (W x H x D) Net Weight	Yes (100mm) UL/CUL, TUV/BAURT, NORDIC, CB, FCC, CE, BSMI, EPA, GOST, WEEE, RoHS DDC 2B, DPMS 100 - 240V, 50 - 60Hz <55W (On) <2W (Stand-by) <1W (Off) 437 x 450 x 196mm (17.2" x 17.7" x 7.7") 555 x 580 x 171mm (21.9" x 22.8" x 6.7") 7.3Kg (16.1lbs)
Mounting Regulation Approval Power Dimensions Weight	VESA FPMPMI Certifications & Compliance VESA Power AC Consumption Net (W x H x D) Packing (W x H x D) Net Weight Gross Weight	Yes (100mm) UL/CUL, TUV/BAURT, NORDIC, CB, FCC, CE, BSMI, EPA, GOST, WEEE, RoHS DDC 2B, DPMS 100 - 240V, 50 - 60Hz <55W (On) <2W (Stand-by) <1W (Off) 437 x 450 x 196mm (17.2" x 17.7" x 7.7") 555 x 580 x 171mm (21.9" x 22.8" x 6.7") 7.3Kg (16.1lbs) 9.5Kg (21.0lbs)

www.agneovo.com

Copyright © 2007 AG Neovo. All rights reserved. The name AG Neovo is a trademark of Associated Industries China, Inc. All other trademarks are the property of their respective owners.