



6 T Equipment Pipe Rail Series

| | |
|--|---|
| • G.V.W.R. - 12,000 # | • Axles - 2-6,000 # cambered brake axles |
| • G.A.W.R.(Each Axle) - 6,000 # | • Suspension - Slipper spring with equalizer |
| • Coupler - 2 - 5/16" adjustable | • Tires - ST 235 / 80R 16" load range D |
| • Safety Chain - 3/8" grade 43 with hooks | • Wheel - 16" 8 bolt white spoke |
| • Jack - 10,000 # drop leg | • Deck - 2" pressure treated pine |
| • Frame - 5" angle w/ H.D.2 1/2" pipe rail | • Lights - D.O.T. stop, tail, turn, and clearance |
| • Crossmembers - 3" channel | • Elec. plug - 7-way RV |
| • Fenders - 10"x72" diamond plate with backs | • Paint - high solids acrylic enamel |
| • Tongue - 6" channel wrap around | • Ramps - 4' fold down |
| • Bed width - 81" | • Sealed modular wiring harness |

Standard Features

Optional Features

| | |
|----------------------------|--------------------------|
| • 16" white spoke | • Steel deck |
| • Pressure treated decking | • 48" split gate |
| • Light protectors | • Self cleaning dovetail |
| • Electric breakaway | • D-Rings |
| • E-Z Lube axles | |

Dimensions

| Length | A | B | C | D | E |
|--------|------|--------|-----|-----|-----|
| 12' | 144" | 95.5" | 43" | 25" | 81" |
| 14' | 168" | 107.5" | 43" | 25" | 81" |
| 16' | 192" | 119.5" | 43" | 25" | 81" |
| 18' | 216" | 131.5" | 43" | 25" | 81" |
| 20' | 240" | 143.5" | 43" | 25" | 81" |
| 22' | 264" | 155.5" | 43" | 25" | 81" |

