

MaxMover





MaxMover

A new ARRI automated stirrup, MaxMover, offers remote pan, tilt and focus for large lighting fixtures. Most large fixtures in your inventory can be fitted to the MaxMover and mounted on boom arms, tall platforms, or in hard-to-reach positions. These fixtures can then be operated safely and conveniently from the ground using a simple analog or optional DMX (wired or wireless) control. A convenient interlock system and variable width adjustment feature allow for a variety of fixtures to be adapted to the MaxMover quickly on location.

At a Glance:

- Automated Stirrup with Universal Adapter Plate
- Variable Width Adjustment
- Accommodates Fixtures from 6kW-24kW
- Quick & Easy Set-up
- 80kg/176lb Capacity
- Remote Control included
- DMX Converter optional

| Cat. No | Description |
|---------|--|
| 563700 | MaxMover; motorized stirrup (for 6kW-24kW ARRI lampheads), includes Universal ARRI Adapter plate, Mega-Claw™ mount, and ARRI analog controller for Pan, Tilt & Focus with 130' (40m) control cable. Includes Roadcase. |
| 563705 | MaxMover Focus Unit; for 6kW-24kW ARRI lampheads |
| 563710 | DMX 512 Converter Control Box |
| 563711 | 25' DMX Control Cable |
| 563712 | 50' DMX Control Cable |
| 563713 | 100' DMX Control Cable |
| 563714 | 5' DMX Control Cable |
| 563715 | DMX 512 Hand Controller |
| 563720 | Adapter Plate for ARRISUN 60 |
| 563725 | Adapter Plate for LTM 12/18kW Fresnel |
| 563726 | Adapter Plate for Mole 12/18kW Fresnel |
| 563727 | Adapter Plate for "Silver Bullet" 12/18kW Fresnel |
| 563735 | Adapter Plate for 12-Light Maxi Brute |
| 563740 | Mitchell Adapter Mount Plate |
| 563790 | Roadcase for MaxMover and Accessories (Included in 563700) |

Specifications

| | |
|----------------------|---|
| Weight | 82lb (37kg) |
| Size | Height 38" (965mm), Width 45.7" (1160mm), Depth 11.8" (300mm) |
| IP Rating | IP54 / Protection class 1 |
| Power Requirements | 90-265V AC, 50/60Hz, 100VA |
| Max. Load | 176lb (80kg) |
| Max. Fixture Width | 34.6" (0.88m) |
| Min. Fixture Width | 21.2" (0.54m) |
| Max. Speed: Pan/Tilt | 360° /min. (1 rpm) |
| Min. Speed: Pan/Tilt | 12.6° /min (0.035 rpm) |
| Max. Speed: Focus | 16 rpm |
| Pivot Range: Pan | Infinite: Adjustable slipping clutch stop (0-80Nm) |
| Pivot Range: Tilt | Infinite: Adjustable slipping clutch stop (0-80Nm) |
| Pivot Range: Focus | Infinite: Current overload/torque stops (5Nm) |
| Analog Controller | ARRI Analog Controller for Pan, Tilt, & Focus (Standard) |
| DMX Controller | Addressable Hand Controller (Optional) |
| DMX Interface | DMX 512 Converter Control Box (Optional) |
| DMX Address | Converter Box Assignment Buttons (Up/Down) |
| DMX Display | Converter Box Address Display Window |



34.6" (880mm)
21.2" (540mm)

For Use With:

ARRIMAX 18/12
ARRI 18/12 HMI Fresnel
ARRI 12000 HMI Fresnel
ARRI 6000 HMI Fresnel
ARRI 6000 Theatre Fresnel
ARRISUN 120
ARRISUN 60
(needs 563720)
ARRI X 60
ARRI T24
ARRI T12
ARRI T12 Theatre
LTM 12/18 Fresnel
(needs 563725)
Mole 12/18 Fresnel
(needs 563726)
"Silver Bullet" 12/18 Fresnel
(needs 563727)
12-Light Maxi Brute
(needs 563735)

Specifications are subject to change without notice. © 2006 ARRI Inc. RP-3/2006/2500



USA
ARRI Inc.
New York Office
617 Route 303
Blauvelt, NY
10913-1109
Tel.+1(845)353-1400
Fax+1(845)425-1250
lighting-info@arri.com
www.arri.com

USA
ARRI Inc.
Burbank Office
600 N. Victory Blvd.
Burbank, CA
91502-1639
Tel.+1(818)841-7070
Fax+1(818)848-4028

CANADA
ARRI Canada LTD.
415 Horner Avenue,
Unit 11, Etobicoke
Ontario M8W 4W3
Tel.+1(416)255-3335
Fax+1(416)255-3399

GERMANY
ARNOLD & RICHTER
CINE TECHNIK
GmbH & Co. Betriebs KG
Türkenstrasse 89
D-80799 München
Tel.+49(0)89-3809-0
Fax +49(0)89-3809-1245

GREAT BRITAIN
ARRI (GB) LTD.
2 Highbridge,
Oxford Road
Uxbridge, Middlesex
UB8 1LX
Tel.+44(0)1895-457000
Fax+44(0)1895-457001

ITALY
ARRI ITALIA SRL
Viale Edison 318
I-20099
Sesto S. Giovanni
Milano
Tel.+39(02)262-27175
Fax+39(02)242-1692