

**BANNER**

## **DUO-TOUCH™ SG Two-Hand-Control**

- Dependable switching with no physical pressure required
- Eliminate hand, wrist and arm stress
- Ergonomically designed for use with repetitive operations
- Type IIIC per EN 574 / ISO 13851 & Category 4 per EN 954-1 / ISO 13849-1
- Ease of installation
- Productivity improvement
- Ideal solution for punch presses and others dangerous machines

**DUO-TOUCH™**



**Prevent repetitive stress injuries!**

- Unique patent-pending photoelectric design, with redundant emitter and receiver

- Ergonomic and rugged housing:
  - IP66
  - Immune to ambient light, EMI and RFI interference
  - High excess gain

- Indicator LEDs

- Connector type M12 quick-disconnect or 2 m cable

- Supplies power to 24 Vdc, 115 Vac and 230 Vac

- Model dependant:  
2 or 4 redundant outputs NO + 1 auxiliary NC output

- Available kits:

*ATK-VP6*: 24 Vdc, 2 N.O.

*ATGMK-VP6*: 24 Vdc, 115 Vac,  
4 N.O. + 1 N.C.

*ATHMK-VP6*: 24 Vdc, 230 Vac,  
4 N.O. + 1 N.C.

Kits are available with 2 m cables or connector type M12 quick-disconnect (by adding suffix Q5 to the kit model number)



### **BANNER Engineering Corp.:**

Sensors and equipment for industrial control and automation:

- Photoelectric sensors
- Ultrasonic sensors
- Cables
- Machine safety products
- Laser measurement products
- Inspection products



**Banner Engineering Corp.**  
 9714 10th Avenue North  
 Minneapolis, Minnesota 55441 USA  
 Phone: +1 763 544 3164  
 Fax: +1 763 544 3213  
[sensors@bannerengineering.com](mailto:sensors@bannerengineering.com)  
[www.bannerengineering.com](http://www.bannerengineering.com)