



	Domestic (60Hz)	Part #	Export (50Hz)	Part #
Shape	Square		Square	
Shell Material	Ultralife/Granitex		Ultralife/Granitex	
Length	83 1/4 in		211 cm	
Width	83 1/4 in		211 cm	
Height	35 1/2 in		90 cm	
Corner Radii	16 in		41 cm	
Water Capacity	300 Gallons		1136 Liters	
Seating Capacity	5+		5+	
Dry Weight	610 lbs		277 kg	
Full Weight	3100 lbs		1406 kg	
Pump Brand	HydraMax by Sta-Rite		Aqua-flo	
Pump Motor Size	3.0 Hp		2.0 Hp	
Pumps/Speed	Two/Dual	01562-22A/B	Two/Single	01562-29A/B
Light	1 with optional Dynamic Lighting	01512-003 (O)	1 with optional Dynamic Lighting	01512-003 (O)
Control System	MSPA-MP-D12	01710-1008	MSPA-MP-D11-CE	01710-1008E
Upper Control	Programmable Digital	01560-320	Programmable Digital	01560-320
Auxiliary Upper Control	No		No	
Programmable	Yes		Yes	
Heater	FastFlo 2.7, 4.0, 5.5 kW	01781-20	FastFlo 2.9 Kw	01781-20
Voltage	240		240	
Amperage	50/40/30		16/2X16/32	
Thermostat	Electronic		Electronic	
Skirt	Wood or Synthetic		Wood / Synthetic	
Poly Floor	Yes		Yes	
Gate Valves	4	01522-30	4	01522-30
Selector Valve	0		0	
Plumb Systems	2		2	
Drains	4+Floor	(4) 01510-559 (1) 01510-231	4+Floor	(4) 01510-559 (1) 01510-231
Skimmer	8" Weir	01510-137	8" Weir	01510-137
VCR Jet-Air Adjustable	2	01510-418	2	01510-418
VCR Jet - Rotator	6	01510-415	6	01510-415
Mini Directional in NFJ	0		0	
VCR Mini Directional	11	01510-444	11	01510-444
VCR Mini Rotator	2	01510-445	2	01510-445
Non-Adjustable Euro Jet	2	01510-438	2	01510-438
Ozone	1	01510-201	1	01510-201
Typhoon Jet	1	01510-436	1	01510-436
Total Jets	25		25	
Filter	1 X 75	01561-00	1 x 75	01561-00
Water Treatment System	Crystal Zone Water Management System	03200-06	Crystal Zone Water Management System	03200-06E
Pillows	3	01510-420	3	01510-420
NeckFlex Jet	0		0	
Dynamic Massage Sequencer	No		No	

Note: Subject to change without notice

2003 Aurora HP, Architectural Specification



Caution:

Due to manufacturing tolerances there could be some minor differences between the actual spa and the drawing above. If site planning is critical to such tolerances, be sure to measure your actual spa.

Note:

1. Subject to change without notice.
2. Engineering specs may differ slightly from brochure.
3. For E-Z Lifter installation allow 18" clearance on the backside of the spa.
4. Alternative cabinets may add significant weight. Ask your dealer for exact details.
5. This is the approximate location for drilling a hole if you must bring the power line in through the bottom of the spa. Be careful not to puncture a plumbing line inside the equipment compartment (drill from the inside Compartment out)