

# STRONG

## Digital HD Satellite Receiver

### SRT 7008



## Discover STRONG receiving technology!

Access free DTT channels in high definition thanks to the new Free-To-Air HD SRT 7008 satellite terminal. In addition to its modern design, the SRT 7008 has compelling features for every viewer's needs: a USB port for the playback of files, 8 programmable timers remind you of your favourite programmes. But also other functions such as the Electronic Programme Guide, parental controls and channel editor. Thanks to the STRONG advanced reception technology, upgrade the functionality of your decoder by adding recording and Timeshift function (available at our webshop).

- HDTV receiver for digital Free-To-Air TV and radio programmes via satellite<sup>1</sup>
- Supports Dolby® Digital Plus<sup>2</sup>
- USB port for playback of files and software updates<sup>3</sup>
- Upgrade your receiver functionality by adding the recording and Timeshift function (available at our webshop)
- Supports SatCR for connecting up to 8 receivers to 1 SatCR LNB
- 4000 channels/64 satellites memory capacity
- Exceptional picture quality and excellent sound
- Electronic Programme Guide (EPG) for on-screen information of present/next events for up to 7 days<sup>4</sup>
- Booking of events directly from EPG



USB  
playback



4000  
channels



Digital  
audio



Favourite  
lists



Energy  
saving

DVB-S2

HDMI

Dolby Audio

DiSEqC1.2

GotoX

eco  
Standby

SatCR  
supported

## Digital HD Satellite Receiver SRT 7008

- HDTV receiver for digital Free-To-Air TV and radio programmes via satellite<sup>1</sup>
- Supports Dolby® Digital Plus<sup>2</sup>
- USB port for playback of multimedia files and software updates<sup>3</sup>
- Upgrade your receiver functionality by adding the recording and Timeshift function (available at our webshop)
- Supports SatCR for connecting up to 8 receivers to 1 SatCR LNB
- 4000 channels/64 satellites memory capacity
- Exceptional picture quality and excellent sound
- Electronic Programme Guide (EPG) for on-screen information of present/next events for up to 7 days<sup>4</sup>
- Booking of events directly from EPG
- Up to 8 programmable timers
- Power saving: switches to standby after a definable time
- Fast and easy channel database up/download to/from USB device
- Teletext and full multi-lingual DVB subtitles supported<sup>4</sup>

- Multiple audio track support<sup>4</sup>
- 8 favourite lists for TV and radio channels
- Parental control for locking selected channels with a password
- Multi-lingual On Screen Display (OSD)
- Easy to use channel handling options for finding, editing, moving, favouring and locking of channels
- Power on with the last viewed channel
- Video output via: HDMI
- Digital audio output via S/PDIF coaxial for connection to a digital amplifier
- Automatic, network and manual channel scan options
- Supports MPEG-4 and H.264
- Supports DiSEqC 1.0, 1.1, 1.2, GOTO X, SatCR
- **Connections:** SAT IN, USB, HDMI, S/PDIF coaxial, DC power
- **Accessories:** Remote control, 2x AAA batteries, power adapter

<sup>1</sup> Subject to your local signal conditions

<sup>2</sup> Dolby Digital Plus, Dolby and the double-D symbol are registered trademarks of Dolby Laboratories

<sup>3</sup> STRONG cannot guarantee the playback of video files although extensions are listed, as it depends on codec used, data bit rate and resolution (all MPEG codec formats are supported).

<sup>4</sup> Availability depending on broadcaster



1. Satellite antenna
2. Ethernet
3. TV (HDMI)

4. Digital audio amplifier
5. Power adapter

### Demodulator

Demodulation: QPSK, 8PSK  
 Input symbol rate: DVB-S QPSK: 1 ~ 45 Ms/s  
 DVB-S2 8PSK/QPSK: 10~30 Ms/s  
 FEC decoder: Auto, 1/2, 2/3, 3/4, 5/6, 7/8 in DVB-S mode  
 1/2, 3/5, 2/3, 3/4, 4/5, 5/6, 8/9, 9/10 in DVB-S2 mode  
 3/5, 2/3, 3/4, 5/6, 8/9, 9/10 in 8PSK mode

### Video Decoder

Input rate: Max. 20 Mbit/s  
 Aspect ratio: 16:9 widescreen, Pillarbox, 4:3 Pan&Scan, Letterbox  
 Video resolution: PAL 50Hz: 576i, 576p, 720p, 1080i, 1080p

NTSC 60Hz: 480i, 480p, 720p, 1080i, 1080p

### Audio Decoder

Audio decoding: MPEG-1 Layer 1 & 2, AC3, Dolby Digital Downmix  
 Audio mode: Mono L/R, Stereo  
 Audio support: E-AC3, Dolby Digital, Dolby Digital Plus<sup>\*</sup>  
 Sampling rate: 32, 44.1, 48 kHz

### Tuner

Type: Type1 F Type, IEC169-24, Female  
 Input frequency range: 950 – 2150 MHz  
 RF impedance: 75 Ohm unbalanced  
 Signal level: -65 to -25 dBm  
 LNB power: 13/18 V DC (+/- 5%), max. 0.5 A, overload protected

Switch versions: DiSEqC 1.0, 1.1

LNB options: Universal, SatCR (max. 8 users)

Motor drive options: DiSEqC 1.2, GotoX (DiSEqC 1.3)

### System & memory

Main processor: MSTAR MSD7501  
 Flash memory: 4 MB  
 System memory: 64 MB

### Connectors

SAT IN  
 USB 2.0 port: 5 V/800 mA (max.) supported  
 HDMI  
 S/PDIF (coax.)  
 Power adapter (12 V, 1.5 A)

### General Data

Power supply: AC 100 – 240 V ~ 50/60 Hz  
 Input voltage: DC 12 V, 1.5 A  
 Power consumption: max. 18 W, typ. 5 W  
 Power consumption in standby: max. 0.5 W  
 Operating temperature: 0 ~ +40°C  
 Storage temperature: -10 ~ +50°C  
 Operating humidity range: 10 ~ 85% RH, non-condensing  
 Size (W x D x H) in mm: 168 x 105 x 37  
 Weight in kg: 0.30

\* Dolby Digital Plus and the double-D symbol are registered trademarks of Dolby Laboratories

EAN SRT 7008 : 9120072372223

| SERVICE CENTER |  |
|----------------|--|
| AT             | support_at@strong.tv<br>0820 400 150<br>(€ 0.12/Min. oöstr. Festnetz)  |
| DE             | support_de@strong.tv<br>0180 501 49 91<br>(€ 0.14/Min. deutsches Festnetz)<br>(€ 0.42/Min. max. Mobilfunknetz)   |
| IT             | support_it@strong.tv<br>199 404 032<br>Da rete fissa 24,8 cent. al min.<br>12,5 cent. scatto alla risposta<br>Da rete mobile max 49 cent. al min.<br>15,6 cent. scatto alla risposta |
| BG             | support_bg@strong.tv<br>+359 32 634451   |
| DK             | support_dk@strong.tv   |
| NL             | support_nl@strong.tv   |
| FR             | support_fr@strong.tv   |
| CEE            | support_hu@strong.tv<br>+36 1 445 26 10  |
| PL             | support_pl@strong.tv<br>801 702 017  |
| UA             | support_ua@strong.tv<br>+380 (44) 238 61 50  |

Subject to alterations. In consequence of continuous research and development technical specifications, design and appearance of products may change. HDMI, the HDMI logo and High-Definition Multimedia Interface are trademarks or registered trademarks of HDMI Licensing LLC in the United States and other countries. Manufactured under license from Dolby Laboratories. Dolby Audio, Dolby Digital, Dolby Digital Plus and the double-D symbol are trademarks of Dolby Laboratories. All product names are trademarks or registered trademarks of their respective owners.  
 © STRONG 2020. All rights reserved.