



Air Conditioners/ Heat Pumps

High Efficiency



Seet 2ACIA(RI)

2AC14(B,L) 2HP14(B,L)

Air Conditioners / Heat Pumps High Efficiency







Save Energy, Save Money

Our air conditioners and heat pumps have a 14 SEER rating* to provide exceptional heating and cooling performance. They are designed to help you use significantly less energy than units installed as recently as five years ago.

Built To Last

Attractive louvered panels protect the coils and are easy to service, while the compressors are designed for reliable and efficient money-saving performance. Our field-proven, adjustable time / temperature defrost control ensures peak performance is maintained during freezing temperatures. Factory-installed, bi-flow liquid line filter driers protect the compressor from contaminants. The corrosion-resistant cabinet is built from strong, heavy-gauge prepainted steel and has drain holes to quickly remove standing water.

Air Conditioner Unit Dimensions

Model Number	Width (Inches)	Depth (Inches)	Height (Inches)
2AC14(B,L)18P	30	30	26
2AC14(B,L)24P	30	30	26
2AC14(B,L)30P	30	30	34
2AC14(B,L)36P	30	30	34
2AC14(B,L)42P	30	30	42
2AC14(B,L)48P	30	30	42

Heat Pump Unit Dimensions

Model Number	Width (Inches)	Depth (Inches)	Height (Inches)
2HP14(B,L)18P	30	30	26
2HP14(B,L)24P	30	30	26
2HP14(B,L)30P	30	30	30
2HP14(B,L)36P	30	30	30
2HP14(B,L)42P	30	30	42
2HP14(B,L)48P	30	30	42













Design Features

- 14 SEER or up to 15 SEER*
- 8.2 HSPF when matched with a variable speed indoor section*
- 1-1/2 4 tons nominal capacity
- Quiet, durable compressor is safeguarded by internal pressure relief valves and inherent thermal protection
- Two coil guard protection options available:
 - Louvered panels provide full metal coil guard ("L"models)
 - Naltex® Hail Guard™ protects from fin damage ("B" models)
- High-quality condenser coils use copper tubes with enhanced louvered fins for maximum heat transfer capability
- Equipped with field-proven 30 / 60 / 90 adjustable time / temperature defrost control
- Permanently lubricated condenser fan motor needs no annual maintenance
- 10-year limited warranty on compressor and 5-year limited warranty on parts**
- Hinged control panel for simple access to internal components
- Angled service valves allow easy access
- Bi-flow liquid line filter drier protects every unit
- Charged for 15 feet of line set
- All models ETL-, ETLC-, and ARI-listed
- *With specified matched system
- **See your local independent dealer for complete details regarding warranty coverage.