LINKSYS®

ProConnect® Compact KVM Switches

Control Multiple PCs with a Single Keyboard, Monitor, and Mouse

Switch PCs with the Touch of a Button!

Linksys's ProConnect KVM Switches allow you to instantly toggle between multiple PS/2-equipped desktop or notebook PCs while using a single monitor, PS/2 keyboard, and PS/2 mouse. Switch between PCs with the press of a button. Plug your notebook PC into the KVM Switch and control it from your desktop PC's monitor, keyboard, and mouse. Built to last and ready to run directly out of the box, Linksys's ProConnect Compact KVM Switches eliminate cable swapping while saving you desktop space and hundreds of dollars of hardware costs. Because they don't use software, the ProConnect Compact KVM Switches are compatible with all major desktop and notebook computers. They're the perfect choice for the home, the office, or anywhere else you manage multiple PCs.

2-Port Compact KVM Switch PS2KVM2 (Left)
4-Port Compact KVM Switch PS2KVM4 (Right)
2-Port Compact KVM Switch Kit PS2KVMSK (not Pictured)

Benefits

Control Multiple PCs from a Single Monitor, PS/2 Keyboard and PS/2 Mouse

Toggle Between PCs with a Single Button or Hot Keys

Save Space, Energy and Hardware Costs

Serves as a Quick Docking Station for Notebook Computers

Simplify the Control of Your Servers

No Software Required

Features

- Control Multiple Computers from a Single Keyboard, Monitor, and Mouse
- Switch Instantly Between PCs
- Save Hundreds of Dollars in Equipment and Energy Costs
- Serves as a Quick Docking Station for Notebook Computers
- Supports an Incredible 1920 x 1440 Maximum Screen Resolution
- Full Plug-and-Play Monitor Support
- Caps Lock, Number Lock, and Scroll Lock Settings Are Automatically Recalled for each PC
- Runs with Most PS/2 and Windows 95 Keyboards
- Compatible with Virtually All Major PS/2 Mice
- No Software Required
- Free Technical Support
- 1-Year Limited Warranty

Specifications

Model Number	2-Port Switch: PS2KVM2 4-Port Switch: PS2KVM4 Switch Kit: PS2KVMSK
Standards	PS/2
Protocol	Microsoft PS/2 Protocol

Ports	*Keyboard*: 1 PS/2 female - Console
	                  2 PS/2 female - CPU
	Mouse: 1 PS/2 female - Console
	                  2 PS/2 female - CPU
	Video: 1 HDB-15 female - Console
	                  2 HDB-15 male - CPU Ports

LED Indicators	2-Port Switch: PC 1, PC 2 4-Port Switch: PC 1, PC 2, PC 3, PC 4
Resolution	Max 1920 x 1440 at 85Hz, DDC2B
Scan Interval	3 seconds

Environmental

Dimensions	2-Port Switch: 4.3 x 3.9 x 1.4 inches 4-Port Switch: 5.1 x 3.9 x 1.4 inches
Weight	2-Port Switch: 4.8 oz. 4-Port Switch: 6.1 oz.
Power Input	DC 5V 20mA (max)
Certifications	FCC Class B, CE Mark Commercial
Operating Temp.	9° F to 72° F (5° C to 40° C)
Storage Temp.	9° F to 72° F (-10° C to 60° C)
Operating Hum.	0% to 80% Non-condensing
Storage Hum.	0% to 80% Non-condensing

Package Contents

2-Port Compact KVM Switch
• One 2-Port Compact KVM Switch
• One User Guide and Registration Card

4-Port Compact KVM Switch
• One 4-Port Compact KVM Switch
• One User Guide and Registration Card

2-Port Compact KVM Switch Kit
• One 2-Port Compact KVM Switch
• Two Keyboard, Video, and Mouse Cables (PS/2)
• One User Guide and Registration Card

LINKSYS®