

New Holland Trailing Wheel Rake Specifications

HT152 HT154



MODEL	HT152 Standard				HT154 Deluxe		
	8-wheel	10-wheel	12-wheel	14-wheel	16-wheel	18-wheel	20-wheel
Max. working width	17'5" (5.3 m)	20'4" (6.2 m)	25' (7.6 m)	28'6" (8.7 m)	30'10" (9.4 m)	33'5" (10.2 m)	36' (11 m)
Transport width8'3" (2.5 m).....	8'3" (2.5 m).....				
Overall height6'3" (1.9 m).....	6'3" (1.9 m).....				
Tire size205-75 x 15".....	205-75 x 15".....				
Number of raking wheels	8	10	12	14	16	18	20
Raking wheel diameter55" (140 cm).....	55" (140 cm).....				
Number of tines/wheels40.....	40.....				
Max. field operating speed14 mph (22.5 kph).....	14 mph (22.5 kph).....				
Min. required tractor hp	30 (22 kW)	30 (22 kW)	30 (22 kW)	40 (30 kW)	40 (30 kW)	55 (41kW)	55 (41kW)
Weight	2425 lbs (1100 kg)	2750 lbs (1247 kg)	3400 lbs (1542 kg)	4400 lbs (1996 kg)	4470 lbs (2028 kg)	5210 lbs (2363 kg)	5540 lbs (2514 kg)

Visit our Web site at www.newholland.com/na. Or, call toll-free **866-NEW-HLND (866-639-4563)**.

Design, materials and/or specifications are subject to change without notice and without liability therefor. Specifications are applicable to units sold in Canada, the United States, its territories and possessions, and may vary outside these areas.



Safety begins with a thorough understanding of the equipment. Always make sure you and your operators read the Operator's Manual before using the equipment. Pay close attention to all safety and operating decals and never operate machinery without all shields, protective devices and structures in place.