Road Worthy, Shop Tested, OEM Approved: Truck Line Adhesives

Urethane Adhesives

SMC/FRP Fiberglass Repair and Panel Bonding

400ml 1:1 Cartridge

PART NUMBER	OEM APPROVED PLIOGRIP® NO.	OPEN TIME	WORK TIME	CLAMPING OR FIXTURE TIME	SANDING OR PAINTING TIME	
04671	7773	3 minutes	3-1/2 minutes	10 minutes	30 minutes	
04672	7779	10 minutes	17 minutes	30 minutes	1 hour	
04673	7770	35 minutes	50 minutes	1-1/2 hours	3 hours	

USE APPLICATOR GUN #41398-MANUAL OR #41396-PNEUMATIC. USE 18 ELEMENT MIXING NOZZLE #04627

600ml 1:1 Cartridge

PART NUMBER	OEM APPROVED PLIOGRIP® NO.	OPEN TIME	WORK TIME	CLAMPING OR FIXTURE TIME	SANDING OR PAINTING TIME
04677	7773	3 minutes	3-1/2 minutes	10 minutes	30 minutes
04678	7779	10 minutes	17 minutes	30 minutes	60 minutes
04679	7770	35 minutes	50 minutes	90 minutes	3 hours
IISE APPLICATOR GIIN #41397-PNFIIMATIC IISE 18 FLEMENT MIXING NO77LE #04627					

temperatures decrease.

OEM APPROVED

SMC/FRP Fiberglass Repair

Fiberglass Matting Adhesive

■ A low viscosity two-part urethane used to saturate fiberglass cloth when

preparing backup patches ■ The self-leveling feature allows the Matting Adhesive to be used for filling

cracks and channels as well **Fiberglass Mat**

■ For reinforcing SMC, FRP and fiberglass repairs

■ Perfect for large repairs where extra reinforcement is needed

Fiberglass and SMC Cloth

■ Excellent for any backup repair – large or small

■ Conforms to any shape





USE APPLICATOR GUN #41398-MANUAL OR #41396-PNEUMATIC. USE 24 ELEMENT MIXING NOZZLE #04628.

Epoxy Adhesives

SMC/FRP Fiberglass Panel Bonding



400ml 2:1 Cartridge

04674 USE APPLICA	04674Epoxy Panel Bonding Adhesive90 minutes4 hours8 hoursUSE APPLICATOR GUN #41398-MANUAL OR #41396-PNEUMATIC. USE 24 ELEMENT MIXING NOZZLE #04628. GLASS BEADS FOR ADEQUATE SPACING.							
Times will increase as temperatures decrease. Times shown above are at 77f/25c. Full cure time is 24 hours but this may be accelerated with heat.								

Rigid Parts Repair and Flexible Plastic Parts Repair

Quickly repair SMC, FRP, fiberglass and plastic parts. Designed for easy sanding and excellent feather edging, these products are a proven adhesive and filler for all rigid and flexible parts. Formulated to finish the front side of repairs used over the top of urethane adhesives.

400ml 1:1 Cartridge

over the SpeedGrip repair area using SpeedGrip

PART NUMBER	DESCRIPTION	WORK TIME	SANDING OR PAINTING TIME
04675	Rigid Parts Epoxy Adhesive	6 mintues	12 minutes
USE APPLICAT	TOR GUN #41398-MANUAL OR #41396-PNEUMATI	C. USE 24 ELEMENT MIXIN	G NOZZLE #04628
400ml 1:	1 Cartridge		

PART NUMBER	DESCRIPTION	WORK TIME	SANDING OR PAINTING TIME
04676	Flexible Parts Epoxy Adhesive	6 mintues	12 minutes
04625	Adhesion Promoter for TPO Repair	-	-




#04675 #04676

Applicator Gun and Mixing Nozzle Guide

NORTON OFFERING	PART Number	SIZE	18 ELEMENT MIXING NOZZLE	24 ELEMENT MIXING NOZZLE	PNEUMATIC GUN 400 ML	MANUAL GUN 400 ML	PNEUMATIC GUN 600 ML
Epoxy Panel Bonding Adhesive	04674	400ml	#04627	# 04628 •	#41396 •	#41398	#41397
Epoxy Rigid Repair Adhesive and Filler	04675	400ml		•		•	
Epoxy Flexible Repair Adhesive and Filler	04676	400ml		•		•	
Fiberglass Matting Adhesive	04680	400ml		•		•	
Urethene Adhesive – 3	04671	400ml	•			•	
Urethene Adhesive – 10	04672	400ml	•			•	
Urethene Adhesive – 35	04673	400ml	•		•	•	
Urethene Adhesive – 3	04677	600ml	•				•
Urethene Adhesive – 10	04678	600ml	•				
Urethene Adhesive – 35	04679	600ml	•				•

Accessories







FOR TECHNICAL HELP: 1 866 879-3761

www.nortonautomotive.com

© Saint-Gobain Abrasives, Inc. February 2007 PLIOGRIP® ADHESIVE Manufactured by Ashland Inc., Columbus, OH • ®PLIOGRIP is a registered trademark of, Ashland Inc. The Norton logo and SpeedGrip are registered trademarks of

Saint-Gobain Abrasives, Inc. **FORM # 7890**



NORTON

