

OSD[®] AUDIO





OUR STORY

Founded in 2003 by a group of audiophiles who understood that good audio products didn't necessarily have to cost an arm and a leg. We started with a small line of outdoor rock speakers that immediately gained attention from consumers who were astounded by the sound quality and reasonable price. We soon expanded our line to include in-wall and ceiling speakers, amplifiers, speaker selectors and more. Eventually we grew to be a market leader for everything home audio, right down to the wire!

Our product line is always expanding for both consumers and installers who appreciate quality products at a great price. We have over 1200 models of speakers, electronics and A/V accessories designed and engineered in the United States and manufactured directly from top-rated ISO 9004 factories. These same factories produce some of world's most famous brand name speakers. OSD Audio found a way to bridge the gap between great sound and affordable pricing, and we are constantly looking for ways to bring even better quality and pricing to customers throughout the world.

Although the company has since grown, we are still a family. OSD Audio is made up of sales, marketing and administrative staff, each with a different job to do but all with the same goal—to ensure that every customer has the best possible experience. Everyone at OSD Audio believes that customers come first. Unlike other companies, we won't hide behind automated voice mail systems and complicated email processes. Our staff is available to answer questions and to provide technical support and personal customer service.

Dave Chai

DAVE CHAI - President

CONTENTS

IN-CEILING	7
IN-WALL	17
MULTIMEDIA	24
SUBWOOFER	26
OUTDOOR	29
AMPLIFIERS	40
SPEAKER SELECTORS	42
VOLUME CONTROL	44
MOUNTS	47
CABLES & WIRE	55
ACCESSORIES	60

MK SERIES IN-CEILING SPEAKERS

OSD Audio's top-of-the line MK Series In-Ceiling Speakers combine elegant design with outstanding audio performance. Often used in dedicated home theaters or high-end whole house audio systems, the MK Series includes Kevlar or Polypropylene woofers in 8" and 6.5" cone sizes. Each model includes butyl rubber surround for audiophile sound and long-lasting construction, a 1" pivoting aluminum or titanium tweeter, bass and treble contour switches, and an advanced crossover network. The line also includes trimless thin bezel models for stealthy installation, angled speakers for less than ideal room layouts, and a dual voice coil version for tight spaces like hallways and bathrooms.

KEY FEATURES



Kevlar Woofers

- High strength-to-weight ratio
- Responds note for note without coloration
- Easily handles high volume levels



Pivoting Tweeters

- Premium materials for the smoothest response
- Enjoy spine-tingling high notes
- Pivots to accommodate room layout



EQ Switches

- Bass and Treble note control
- Tailor sound to personal taste
- Compensate for hard and soft surfaces



Custom Crossovers

- 12dB crossover network
- Engineered with premium components
- Directs frequencies with pin-point accuracy



MK850

8" Kevlar Woofer
1" Pivoting Aluminum Tweeter
Butyl Rubber Surround
Bass / Treble Contour Switches
Power handling: 200W
Freq Response: 25Hz - 22kHz
Sensitivity: 92db
Impedance: 8 ohms



MK840

8" Polypropylene Woofer
1" Pivoting Titanium Tweeter
Butyl Rubber Surround
Bass / Treble Contour Switches
Power handling: 175W
Freq Response: 32Hz - 22kHz
Sensitivity: 92db
Impedance: 8 ohms



MK650

6.5" Kevlar Woofer
1" Pivoting Aluminum Tweeter
Butyl Rubber Surround
Bass / Treble Contour Switches
Power handling: 175W
Freq Response: 28Hz - 22kHz
Sensitivity: 92db
Impedance: 8 ohms



MK640

6.5" Polypropylene Woofer
1" Pivoting Titanium Tweeter
Butyl Rubber Surround
Bass / Treble Contour Switches
Power handling: 150W
Freq Response: 32Hz - 22kHz
Sensitivity: 92db
Impedance: 8 ohms



MK670

6.5" Angled Kevlar Woofer
1" Pivoting Aluminum Tweeter
Butyl Rubber Surround
Fixed 15 Degree Angle
Power handling: 175W
Freq Response: 30Hz - 22kHz
Sensitivity: 92db
Impedance: 8 ohms



MK690TT

8" Kevlar Woofer
1" Pivoting Aluminum Tweeter
Trimless Thin Bezel
Butyl Rubber Surround
Bass / Treble Contour Switches
Power handling: 200W
Freq Response: 25Hz - 22kHz
Sensitivity: 92db
Impedance: 8 ohms

PRO SERIES IN-CEILING SPEAKERS

OSD Audio's Pro Series Ceiling Speakers are moderately priced and popular for both home theaters and whole house audio. Several models use a dual voice coil design for smaller spaces that may not accommodate multiple speakers. The Pro Series also includes an angled LCR speaker that provides remarkable imaging in less than ideal room layouts. Other features include polypropylene cone woofers with butyl rubber surround and pivoting silk dome tweeters for excellent high and low frequencies in any application.

KEY FEATURES



Poly Woofers

- Polypropylene cone with butyl rubber surround
- Easily handles high volume levels
- Superb bass response and sensitivity



Pivoting Tweeters

- Adjustable Silk Dome Tweeter
- Enjoy crisp high notes and smooth vocals
- Aim high frequencies toward the sweet spot



High Quality

- High quality over crossover for excellent sound reproduction
- Butyl rubber surround increases longevity
- Gold-plated compression posts



ICE840

8" Polypropylene woofer
1" Pivoting Silk Tweeter
Butyl Rubber Surround
Power handling: 175W
Freq Response: 36Hz - 22kHz
Sensitivity: 91db
Impedance: 8 ohms



ICE840TT

8" Polypropylene Woofer
Dual 3/4" Pivoting Silk Tweeters
Butyl Rubber Surround
Dual Voice Coil / Single Stereo
Power handling: 175W
Freq Response: 36Hz - 22kHz
Sensitivity: 89db
Impedance: 16 / 8 ohms



ICE640

6.5" Mica-Filled Polypropylene Woofer
1" Pivoting Silk Tweeter
Butyl Rubber Surround
Power handling: 150W
Freq Response: 38Hz - 22kHz
Sensitivity: 91db
Impedance: 8 ohms



ICE640TT

6.5" Polypropylene Woofer
Dual 3/4" Pivoting Silk Tweeters
Butyl Rubber Surround
Dual Voice Coil / Single Stereo
Power handling: 175W
Freq Response: 40Hz - 22kHz
Sensitivity: 89db
Impedance: 16 / 8 ohms



ICE540

5.25" Polypropylene Woofer
3/4" Pivoting Silk Tweeter
Butyl Rubber Surround
Power handling: 120W
Freq Response: 65Hz - 20kHz
Sensitivity: 91db
Impedance: 8 ohms



ICE660

6.5" Angled Polypropylene Woofer
1" Pivoting Silk Tweeter
Butyl Rubber Surround
Fixed 15 Degree Angle
Power handling: 150W
Freq Response: 50Hz - 22kHz
Sensitivity: 92db
Impedance: 8 ohms

CUSTOM SERIES IN-CEILING SPEAKERS


The Custom Series is an exceptional line of ceiling speakers for use in whole house audio and home theaters on a budget. The Custom Series includes polypropylene woofers with durable butyl rubber surround as well as silk pivoting tweeters for extended highs. In addition to the traditional speaker designs the Custom Series also includes trimless thin bezel models. With a unique balance of solid build and sound quality, while remaining relatively low cost, the Custom Series is a great solution for many home and commercial budget-conscious applications. Like all OSD Audio ceiling speakers, the Custom Series incorporates dog-ear mounting brackets that allow you to secure the speaker directly to the ceiling without special brackets or back boxes.

KEY FEATURES



Poly Woofers

- Polypropylene cone with butyl rubber surround
- Easily handles high volume levels
- Great bass response and sensitivity



Pivoting Tweeters

- Adjustable Silk Dome Tweeter on select models
- Enjoy crisp high notes and smooth vocals
- Aim high frequencies toward the sweet spot



Easy Mounting

- Dog-ear mounting system
- Install with basic tools



ICE810

8" Polypropylene Woofer
1" Pivoting Silk Tweeter
Butyl Rubber Surround
Power handling: 140W
Freq Response: 38Hz - 22kHz
Sensitivity: 89db
Impedance: 8 ohms



ICE800

8" Polypropylene Woofer
1/2" PEI Dome Tweeter
Butyl Rubber Surround
Power handling: 120W
Freq Response: 45Hz - 22kHz
Sensitivity: 90db
Impedance: 8 ohms



ICE620

6.5" Polypropylene Woofer
1" Pivoting Silk Tweeter
Butyl Rubber Surround
Power handling: 100W
Freq Response: 58Hz - 22kHz
Sensitivity: 89db
Impedance: 8 ohms



ICE620TT

6.5" Angled Polypropylene Woofer
Dual 1" Silk Tweeters
Butyl Rubber Surround
Dual Voice Coil / Single Stereo
Power handling: 125W
Freq Response: 40Hz - 22kHz
Sensitivity: 89db
Impedance: 8 ohms



ICE530

5.25" Polypropylene Woofer
3/4" Pivoting Silk Tweeter
Butyl Rubber Surround
Power handling: 100W
Freq Response: 65Hz - 22kHz
Sensitivity: 88db
Impedance: 8 ohms



ICE610

6.5" Polypropylene Woofer
3/4" Polyamide Tweeter
Butyl Rubber Surround
Power handling: 100W
Freq Response: 60Hz - 22kHz
Sensitivity: 90db
Impedance: 8 ohms



ACE590

Trimless Design
6.5" Polypropylene Woofer
3/4" Polyamide Tweeter
Power handling: 100W
Freq Response: 62Hz - 20kHz
Sensitivity: 89db
Impedance: 8 ohms



ACE500

Trimless Design
5.25" Polypropylene Woofer
3/4" Polyamide Tweeter
Power handling: 75W
Freq Response: 79Hz - 20kHz
Sensitivity: 89db
Impedance: 8 ohms



ACE400

Trimless Design
3" Full Range Polypropylene Woofer
Power handling: 60W
Freq Response: 120Hz - 20kHz
Sensitivity: 88db
Impedance: 8 ohms

WR SERIES IN-CEILING SPEAKERS

For rooms prone to humidity such as bathrooms, laundry rooms and hot tubs, moisture can cause speaker parts to rust and even stop working after only a few months. OSD Audio's WRS Series of In-Ceiling Speakers is specifically designed for these areas so you can relax in the tub and enjoy beautiful sound. These moisture-resistant speakers have powder-coated grilles and specially treated internal components that withstand humidity and can even be used outside in covered porches. The WRS Series includes polypropylene woofers with santoprene surround and moisture-resistant tweeters for excellent high and low notes; and because bathrooms and laundry rooms are often small, the WRS Series includes models with dual voice coils so you can enjoy stereo sound from only one speaker!

KEY FEATURES



Moisture Resistant

- Specifically for high humidity areas
- Treated to withstand moisture
- Powder coated grilles and sealed internal components



Quality Components

- Polypropylene woofer with Santoprene surround
- Moisture resistant tweeters
- High power handling capability



Multi Application

- Ideal for saunas, bathrooms and laundry rooms
- Enjoy music i high humidity areas
- Perfect for covered porches and patios



ICE800WRS

8" Moisture-Resistant Polypropylene Woofer
1" Moisture-Resistant Tweeter
Santoprene Surround
Weather-Treated Grills
Power handling: 150W
Freq Response: 38Hz - 21kHz
Sensitivity: 90db
Impedance: 8 ohms



ICE600WRS

6.5" Moisture-Resistant Polypropylene Woofer
1" Moisture-Resistant Tweeter
Santoprene Surround
Weather-Treated Grills
Power handling: 150W
Freq Response: 38Hz - 21kHz
Sensitivity: 90db
Impedance: 8 ohms



ICE800TTWRS

8" Moisture-Resistant Polypropylene Woofer
Dual 1" Moisture-Resistant Tweeters
Santoprene Surround
Weather-Treated Grills
Power handling: 150W
Freq Response: 38Hz - 21kHz
Sensitivity: 89db
Impedance: 8 ohms



ICE600TTWRS

6.5" Moisture-Resistant Polypropylene Woofer
Dual 1" Moisture-Resistant Tweeters
Santoprene Surround
Weather-Treated Grills
Power handling: 120W
Freq Response: 48Hz - 20kHz
Sensitivity: 89db
Impedance: 8 ohms

70V COMMERCIAL IN-CEILING SPEAKERS

From restaurants to offices, from theme parks to hotels, OSD Audio has commercial speakers for just about any application. The best part is, you'll pay less than half the price of many of the "designer" brand names but experience equal or better sound quality and durability. Our high-end, backcan-equipped 70v in-ceiling models are very popular for commercial applications that require premium sound quality & top notch aesthetics. In addition to the integrated backcan, these speakers have a built-in 70v transformer with multiple tap settings & are available in both 6.5" & 8" versions. For a more traditional commercial design, check out our rugged C1070V & C1090VK speakers that come fully equipped with 6.5 & 5.25" drivers with 6 oz. magnets and dual 70/25V transformers. No matter the application, the OSD Audio line of commercial in-ceiling speakers continue to be a favorite of the most experienced installers.

KEY FEATURES



High Performance

- ST Series delivers premium sound quality with built-in 70v switch taps, a back-can and home audio styling
- C Series provides dependable audio component in a traditional commercial speaker chassis with integrated 70v transformer



Easy Installation

- Easy access connectors
- Wire guide and clamp mounted on back-can equipped models
- Dog-ear mounting system for easy installation



70V Transformer

- Built-In 70v transformer for easy connecting
- 70v tap offers multiple wattage settings as well as 8ohm option
- Both switch tap and line transformer on select models



ICE840ST

8" Polypropylene woofer
1" Pivoting Silk Tweeter
Butyl Rubber Surround
Power handling: 175W
Freq Response: 36Hz - 22kHz
Sensitivity: 91db
Impedance: 8 ohms



ICE800ST

8" Polypropylene Woofer
Dual 3/4" Pivoting Silk Tweeters
Butyl Rubber Surround
Dual Voice Coil / Single Stereo
Power handling: 175W
Freq Response: 36Hz - 22kHz
Sensitivity: 89db
Impedance: 16 / 8 ohms



ICE620ST

6.5" Mica-Filled Polypropylene Woofer
1" Pivoting Silk Tweeter
Butyl Rubber Surround
Power handling: 150W
Freq Response: 38Hz - 22kHz
Sensitivity: 91db
Impedance: 8 ohms



C1090VK

6.5" Polypropylene Woofer
Dual 3/4" Pivoting Silk Tweeters
Butyl Rubber Surround
Dual Voice Coil / Single Stereo
Power handling: 175W
Freq Response: 40Hz - 22kHz
Sensitivity: 89db
Impedance: 16 / 8 ohms



C1070V

5.25" Polypropylene Woofer
3/4" Pivoting Silk Tweeter
Butyl Rubber Surround
Power handling: 120W
Freq Response: 65Hz - 20kHz
Sensitivity: 91db
Impedance: 8 ohms



MK SERIES IN-WALL SPEAKERS

Our top-of-the line offering in the in-wall speaker category, the OSD Audio MK Series is a popular choice for high-end, dedicated home theaters due to the premium technologies such as Kevlar woofers and aluminum dome tweeters. With advanced crossover networks and high-end components, you'll experience 5.1 or 7.1 Digital Surround Sound like you've never heard before, and each model includes contour switches that let you tailor frequency response to your particular room arrangement. Once you hear the sound quality of our MK In-wall speakers, you'll never want to go out to the movies again.

KEY FEATURES



Kevlar Woofers

- High strength-to-weight ratio
- Responds note for note without coloration
- Easily handles high volume levels



Pivoting Tweeters

- Premium materials for the smoothest response
- Aluminum tweeter provides spine-tingling high notes
- Adjustable tweeter accommodates room layout



EQ Switches

- +/- 3dB Bass and Treble adjustability
- Tailor sound to personal taste
- Compensate for hard or soft surfaces



MK-W850

8" Kevlar Woofer
1" Pivoting Aluminum Tweeter
Butyl Rubber Surround
Bass / Treble Contour Switches
Power Handling: 200W
Freq Response: 25Hz - 22kHz
Sensitivity: 92db
Impedance: 8 ohms



MK-W650

6.5" Kevlar Woofer
1" Pivoting Aluminum Tweeter
Butyl Rubber Surround
Bass / Treble Contour Switches
Power Handling: 175W
Freq Response: 28Hz - 22kHz
Sensitivity: 92db
Impedance: 8 ohms



MK-IW550 LCR

Dual 5.25" Kevlar Woofer
1" Pivoting Aluminum Tweeter
Butyl Rubber Surround
Left, Center or Right Channel
Bass / Treble Contour Switches
Power Handling: 175W
Freq Response: 25Hz - 22kHz
Sensitivity: 90db
Impedance: 8 ohms

PRO SERIES IN-WALL SPEAKERS


OSD Audio's Pro Series In-wall Speakers defy their low price range with features typically found in speakers retailing at double the price. Polypropylene cone woofers reproduce excellent low notes, while pivoting silk dome tweeters serve up those crisp, spine-tingling high frequencies. Popular for both home theaters and distributed audio, the Pro Series includes both traditional rectangular frames, as well as newly popular square frames. Sizes include an 8" model for larger rooms, dedicated home theaters, or rooms with high vaulted ceilings; a 6.5" model for medium to smaller size areas; and a 5.25" in-wall speaker for small rooms like dining areas and kitchens. The Pro Series also includes a dual 5.25" center channel speaker that provides remarkable front stage sound for dedicated home theaters and media rooms; and like all OSD in-wall speakers, the Pro Series includes paintable grills and easy-mount dog-ear brackets.

KEY FEATURES



Poly Woofers

- High-grade material for superior sound quality
- Superb bass response and sensitivity
- High power handling capability



Pivoting Tweeters

- Adjustable Silk Dome Tweeter
- Enjoy crisp high notes and smooth vocals
- Aim high frequencies toward the sweet spot



Quality Components

- High quality crossover for excellent sound reproduction
- Butyl rubber surround increases longevity
- Gold-plated compression posts



IW840

8" Polypropylene Woofer
1" Pivoting Silk Tweeter
Butyl Rubber Surround
Power Handling: 175W
Freq Response: 36Hz - 22kHz
Sensitivity: 90db
Impedance: 8 ohms



IW680

6.5" Polypropylene Woofer
1" Pivoting Silk Tweeter
Butyl Rubber Surround
Power Handling: 150W
Freq Response: 38Hz - 22kHz
Sensitivity: 90db
Impedance: 8 ohms



IW540

5.25" Polypropylene Woofer
3/4" Pivoting Silk Tweeter
Butyl Rubber Surround
Power Handling: 100W
Freq Response: 58Hz - 22kHz
Sensitivity: 90db
Impedance: 8 ohms



CW-840SQ

8" Polypropylene Woofer
1" Pivoting Silk Tweeter
Butyl Rubber Surround
Power Handling: 150W
Freq Response: 36Hz - 20kHz
Sensitivity: 91db
Impedance: 8 ohms



CW-640SQ

6.5" Polypropylene Woofer
1" Pivoting Silk Tweeter
Butyl Rubber Surround
Power Handling: 150W
Freq Response: 38Hz - 20kHz
Sensitivity: 90db
Impedance: 8 ohms



CW-540SQ

5.25" Polypropylene Woofer
1" Pivoting Silk Tweeter
Butyl Rubber Surround
Power Handling: 125W
Freq Response: 58Hz - 20kHz
Sensitivity: 90db
Impedance: 8 ohms



IW545 LCR

Dual 5.25" Polypropylene Woofer
1" Pivoting Silk Tweeter
Butyl Rubber Surround
Left, Center, Right
Power Handling: 125W
Freq Response: 50Hz - 22kHz
Sensitivity: 90db
Impedance: 8 ohms

CUSTOM SERIES IN-WALL SPEAKERS

OSD Audio's Custom Series is an exceptional line of in-wall speakers for use in whole house audio and home theaters on a budget. The Custom Series includes polypropylene woofers with durable butyl rubber surround as well as silk pivoting tweeters for extended highs. With a unique balance of solid build and sound quality, while remaining relatively low cost, the Custom Series is a great solution for many home and commercial budget-conscious applications. Like all OSD Audio in-wall speakers, the Custom Series incorporates dog-ear mounting brackets that allow you to secure the speaker directly to the wall without special brackets or back boxes.

KEY FEATURES



Poly Woofers

- Polypropylene cone with butyl rubber surround
- Easily handles high volume levels
- Great bass response and sensitivity



Pivoting Tweeters

- Adjustable Silk Dome Tweeter on select models
- Enjoy crisp high notes and smooth vocals
- Aim high frequencies toward the sweet spot



Easy Mounting

- Dog-ear mounting system
- Install with basic tools



IW810

8" Polypropylene Woofer
2" Coaxial Mid-Range
1" Pivoting Silk Tweeter
Butyl Rubber Surround
Power Handling: 150W
Freq Response: 38Hz - 22kHz
Sensitivity: 90db
Impedance: 8 ohms



IW530

5.25" Polypropylene Woofer
3/4" Pivoting Silk Tweeter
Butyl Rubber Surround
Power Handling: 100W
Freq Response: 68Hz - 22kHz
Sensitivity: 87db
Impedance: 8 ohms



IW800

8" Polypropylene Woofer
1/2" PEI Dome Tweeter
Butyl Rubber Surround
Power Handling: 120W
Freq Response: 45Hz - 22kHz
Sensitivity: 89db
Impedance: 8 ohms



IW520

5.25" Polypropylene Woofer
1/2" PEI Dome Tweeter
Butyl Rubber Surround
Power Handling: 90W
Freq Response: 75Hz - 22kHz
Sensitivity: 88db
Impedance: 8 ohms

MULTIMEDIA SPEAKERS

OSD Audio's Multimedia Speakers are a great indoor solution for a wide variety of applications. Whether it's surround sound for your living room, speakers for your desktop or large commercial spaces, OSD has you covered. The SS2.1 & SP2.1 SoundPlatform greatly enhances the sound quality of today's flat screen LED, LCD and Plasma TVs without having to add a lot of speakers. A single speaker system that requires very little space, the SoundPlatform can be installed below or in front of a high definition TV or inside a cabinet. You'll enjoy simulated surround sound from a single, space-saving cabinet with deep, enveloping bass without bulky speakers or amps. It easily connects to inputs on today's flat panel TVs and digital music players and even syncs to almost any Bluetooth® audio device. The OSD Audio Pendant Speakers are a great choice for high vaulted ceilings in any large, open space. Pendants deliver a designer aesthetic & high quality sound to any application. The Sphere Speakers are great for homes and offices alike. With a compact design that delivers big sound, you can use them anywhere! The Multimedia Speaker line is yet another great example of the versatility & functionality OSD Audio brings to the table.



KEY FEATURES



Sound Platform

- Syncs directly to any Bluetooth device as well as Optical and RCA connectivity
- Slim and sleek, yet sturdy construction makes for an ideal TV platform



Pendant Series

- 140 degree wide-dispersion coaxial driver for even coverage as well as low-resonance cabinet structure
- Ideal choice for high vault ceilings and large, open spaces
- Great for applications ranging from commercial structures to designer homes



Sphere Speakers

- Compact speakers that deliver big sound
- Excellent desktop or surround speakers
- Classic, modern styling make these a great choice for anything from a professional office to a home media room



SP2.1



SoundPlatform
4.2 Simulated Surround
Bluetooth, Digital & Analog Audio Connectivity
Dual 5.25" Down-Firing Subwoofers
Four 2.5" Midrange Speakers
Dual 1" Silk Tweeters
Bi-Amped, 80 Watts Total Amplification
Includes IR Remote Control
Frequency Response: 35Hz - 20kHz
Supports Max Weight: 85lbs
Matte Black Finish
Multiple Source Inputs: Digital/Analog/
Bluetooth Wireless



SS2.1



SoundSole
2.1 Stereo
Bluetooth Wireless Technology
Two 2.25" Full Range Drivers
Dual 5.25" Down-Firing Sub-Woofer
Bi-Amped, 50 Watts Total Amplification
Includes IR Remote Control
Frequency Response: 45Hz - 20kHz
Supports Max Weight: 55lbs
Matte Black Finish
Multiple Source Inputs: Digital/Analog/
Bluetooth Wireless



SPHERE1

3.5" Paper Woofer
1/2" Silk Tweeter
Power Handling: 100W
Frequency Response: 150Hz - 22kHz
Sensitivity: 85db
Impedance: 4-8 ohms



PC850

8" Polypropylene Woofer
1" Silk Tweeter
140 Degree Sound Dispersion
Power Handling: 150W
Frequency Response: 50Hz - 20kHz
Sensitivity: 89db
Impedance: 8 ohms



PC690

6.5" Polypropylene Woofer
1" Silk Tweeter
140 Degree Sound Dispersion
Power Handling: 100W
Frequency Response: 60Hz - 20kHz
Sensitivity: 88db
Impedance: 8 ohms



PC640

6.5" Polypropylene Woofer
1" Silk Tweeter
140 Degree Sound Dispersion
Integrated 70v Tap
Power Handling: 100W
Sensitivity: 92db
Impedance: 8 ohms



PC540

5.25" Polypropylene Woofer
1" Silk Tweeter
140 Degree Sound Dispersion
Integrated 70v Tap
Power Handling: 60W
Sensitivity: 88db
Impedance: 8 ohms



SUBWOOFERS

Subwoofers provide a solution for a large range of applications. With subwoofer choices spanning from powered down-firing and front-firing to passive in-wall, our aim is to provide a subwoofer solution for nearly any application. Each subwoofer we offer has been designed and engineered with this primary goal in mind. Our second mandate was to build subwoofers that complement the many other products we offer both in price and performance. Whether it's part of a custom home theater, 2.1 Hi-Fi music configuration or whole house distributed audio, we have the perfect sub for you!

KEY FEATURES



Front-Firing

- 12", 10" & Dual 8" woofer options
- Dual 2" front-firing ports on 10" and 12" models
- Extended low frequency range



Down-Firing

- 12", 10" and 8" woofer options
- 3" front-firing port
- Great for hard wood floors



In-Wall

- Sleek and clean aesthetics make for seamless home integration
- Perfect solution to complete your In-Wall/In-Ceiling speaker configuration
- Paintable trim & grilles



PS12

12" Powered Subwoofer
Front-Firing Woofer
Dual 2" Front-Firing Ports
Auto Sensing Feature
Gain, Phase & Crossover Control
Output: 175W @ <1% THD
Freq Response: 25Hz - 180Hz



PS10

10" Powered Subwoofer
Front-Firing Woofer
Dual 2" Front-Firing Ports
Auto Sensing Feature
Gain, Phase & Crossover Control
Output: 125W @ <1% THD
Freq Response: 25Hz - 180Hz



PS88

Dual 8" Powered Subwoofer
8" Long-Throw Front-Firing Woofer & 8" Passive Radiator
Oversized Foam Surround
Auto Sensing Feature
Gain, Phase & Crossover Control
Output: 180W RMS (4 ohm)
Freq Response: 25Hz - 160Hz



S-12

12" Powered Subwoofer
Down-Firing Woofer
3" Front-Firing Port
Auto Sensing Feature
Gain & Crossover Control
Output: 150W (RMS)
Freq Response: 50Hz - 250Hz



S-10

10" Powered Subwoofer
Down-Firing Woofer
3" Front-Firing Port
Auto Sensing Feature
Gain & Crossover Control
Output: 120W (RMS)
Freq Response: 50Hz - 250Hz



P8

8" Powered Subwoofer
Down-Firing Woofer
3" Front-Firing Port
Auto Sensing Feature
Gain & Crossover Control
Output: 100W (RMS)
Freq Response: 50Hz - 250Hz



IWS-10

10" Passive In-Wall Subwoofer
Butyl Rubber Surround
Paintable Trim & Grille
Power Handling: 200W
Freq Response: 38Hz - 200Hz
Sensitivity: 86db
Impedance: 8 ohms



IWS-8W

8" Passive In-Wall Subwoofer
Butyl Rubber Surround
Paintable Trim & Grille
Power Handling: 150W
Freq Response: 40Hz - 200Hz
Sensitivity: 87db
Impedance: 8 ohms



IWS-88

Dual 8" Passive In-Wall Subwoofer
Butyl Rubber Surround
Paintable Trim & Grille
Power Handling: 240W
Freq Response: 45Hz - 500Hz
Sensitivity: 90db
Impedance: 8 ohms



WIRELESS OUTDOOR

Using the latest wireless Bluetooth technology, OSD Audio Wireless Outdoor Speakers are a reliable and easy way to deliver excellent audio anywhere throughout your property. These all-weather speakers are available in both traditional patio designs, as well as rocks. The Bluetooth speakers sync directly to any Bluetooth-enabled devices, such as your mobile phone or tablet and have a range of up to 150 feet (unobstructed). No matter which model suits your particular application best, within minutes you'll enjoy high definition sound without having to run cables from your audio source to your speakers.



KEY FEATURES



Bluetooth

- Syncs directly to any Bluetooth device
- Simple & reliable high-quality connection
- Both indoor & outdoor offerings available



Durable

- Up to 150 foot range
- Sturdy weather-resistant enclosures
- Weather-protected grilles and sealed internal components



Easy Install

- AC or battery powered (select models)
- Quick setup and pairing with any bluetooth device



BTR-800

8" Polypropylene Woofer
1" Tweeter
Butyl Rubber Surround
Bluetooth Source Connectivity
Compatible with A2DP Standard
Bluetooth Range: 120' to 150' (unobstructed) / 50' to 75' (obstructed)
Output: 100W
Freq Response: 28Hz - 20kHz
Impedance: 8 ohms
Colors: Slate Gray, Brown



BTR-800TT

8" Polypropylene Woofer
Dual 2" Tweeters
Single Stereo / Dual Voice Coil
Bluetooth Source Connectivity
Compatible with A2DP Standard
Bluetooth Range: 120' to 150' (unobstructed) / 50' to 75' (obstructed)
Output: 100W
Freq Response: 35Hz - 20kHz
Sensitivity: 88db
Impedance: 8 ohms
Colors: Slate Gray, Brown



BTR-150

5.25" Polypropylene Cone
Bluetooth Source Connectivity
Compatible with A2DP Standard
Bluetooth Range: 120' to 150' (unobstructed) / 50' to 75' (obstructed)
Output: 20W RMS / 50W Peak
Freq Response: 90Hz - 20kHz
Impedance: 8 ohms
Optional 12 volt (6 AA Batteries)
Colors: Slate Gray, Brown



BTP-650

6.5" Polypropylene Woofer
1" Tweeter
Butyl Rubber Surround
Bluetooth Source Connectivity
Compatible with A2DP Standard
Bluetooth Range: 120' to 150' (unobstructed) / 50' to 75' (obstructed)
Output: 100W
Freq Response: 38Hz - 20kHz
Impedance: 8 ohms
Colors: White, Black



BTF-525

5.25" Polypropylene Cone
Bluetooth Source Connectivity
Compatible with A2DP Standard
Bluetooth Range: 120' to 150' (unobstructed) / 50' to 75' (obstructed)
Output: 20W RMS / 50W Peak
Freq Response: 90Hz - 20kHz
Impedance: 8 ohms
Optional 12 volt (6 AA Batteries)

OUTDOOR ROCKS

Top of the line in the outdoor speaker category, OSD Audio's Rock Speakers deliver amazing sound in backyards, gardens or any type of landscape. Built with audiophile-grade components and aerospace-grade enclosures, these all weather speakers withstand rain, snow, extreme temperatures, and other harsh weather conditions. Integrating seamlessly into any outdoor environment with their realistic rock appearance, the RS & RX series offer a wide range of models to fit your application. The RS series is perfect for providing high definition sound throughout a medium to large sized area, where as the RX series offers a solid alternative for the small to medium sized application on a budget. All OSD Audio Rock Speakers are available in a variety of brown & gray finishes to match your backyard setting.

KEY FEATURES




RS Series

- Audiophile-grade components, high power handling, and weather-proof 8" and 6.5" 2-way drivers
- Aero-space grade Multi-layer Cabinetry, weather-protected grilles and sealed internal components
- Produces deep, rich bass and crystal clear high notes



RX Series

- High quality internal components with 5.25" weather-proof 2-way drivers
- Aero-space grade Multi-layer Cabinetry, weather-protected grilles and sealed internal components
- Ideal for small to medium sized applications



Omni & DVC Models

- Single stereo DVC (dual voice coil) speakers for stereo sound in a single speaker
- Omni speakers for 360 degree sound dispersion
- Aero-space grade Multi-layer Cabinetry, weather-protected grilles and sealed internal components



RS850

8" Polypropylene Woofer
2" Polyamide Tweeter
Butyl Rubber Surround
Durable Composite Cabinet
Integrated Water Drainage
Power Handling: 300W
Freq Response: 20Hz - 20kHz
Sensitivity: 91db
Impedance: 8 ohms
Finishes: Brown & Gray



RS840

8" Polypropylene Woofer
1.5" Polyamide Tweeter
Butyl Rubber Surround
Durable Composite Cabinet
Integrated Water Drainage
Power Handling: 250W
Freq Response: 24Hz - 20kHz
Sensitivity: 92db
Impedance: 8 ohms
Finishes: Brown & Gray



RS8200M

10" Powered Subwoofer
Front-Firing Woofer
Dual 2" Front-Firing Ports
Auto Sensing Feature
Gain, Phase & Crossover Control
Output: 125W @ <1% THD
Freq Response: 25Hz - 180Hz



RS810

8" Polypropylene Woofer
1" Polyamide Tweeter
360 Degree Sound Dispersion
Durable Composite Cabinet
Power Handling: 250W
Freq Response: 34Hz - 20kHz
Sensitivity: 90db
Impedance: 8 ohms
Finishes: Sandstone Brown, Granite Gray & White Granite



RS800

8" Polypropylene Woofer
2" Polyamide Tweeter
Butyl Rubber Surround
Durable Composite Cabinet
Integrated Water Drainage
Power Handling: 200W
Freq Response: 38Hz - 20kHz
Sensitivity: 91db
Impedance: 8 ohms
Finishes: Brown & Gray



RS850TT

8" Polypropylene Woofer
Dual 1" Tweeters
Single Stereo / Dual Voice Coil
Durable Composite Cabinet
Power Handling: 400W
Freq Response: 28Hz - 21kHz
Sensitivity: 89db
Impedance: 8 ohms
Finishes: Brown & Gray



RS800TT

8" Polypropylene Woofer
Dual 2" Tweeters
Single Stereo / Dual Voice Coil
Durable Composite Cabinet
Power Handling: 200W
Freq Response: 35Hz - 20kHz
Sensitivity: 88db
Impedance: 8 ohms
Finishes: Brown & Gray



RS690TT

6.5" Polypropylene Woofer
Dual 1" Tweeters
Single Stereo / Dual Voice Coil
Durable Composite Cabinet
Power Handling: 120W
Freq Response: 60Hz - 20kHz
Sensitivity: 90db
Impedance: 8 ohms
Finishes: Brown & Gray



RS690

6.5" Polypropylene Woofer
1" Polyamide Tweeter
Butyl Rubber Surround
Durable Composite Cabinet
Power Handling: 175W
Freq Response: 30Hz - 20kHz
Sensitivity: 91db
Impedance: 8 ohms
Finishes: Brown & Gray



RS670-JR

6.5" Polypropylene Woofer
1" Polyamide Tweeter
Butyl Rubber Surround
Durable Composite Cabinet
Power Handling: 150W
Freq Response: 45Hz - 20kHz
Sensitivity: 90db
Impedance: 8 ohms
Finishes: Sandstone Brown, Granite Gray, Slate Gray & White Granite



RX550

5.25" Polypropylene Driver
Durable Composite Cabinet
Power Handling: 100W
Freq Response: 65Hz - 20kHz
Sensitivity: 88db
Impedance: 8 ohms
Finishes: Canyon Brown, Slate Gray & White Granite



RX540

5.25" Polypropylene Driver
3/4" Tweeter
Durable Composite Cabinet
Power Handling: 80W
Freq Response: 75Hz - 20kHz
Sensitivity: 89db
Impedance: 8 ohms
Finishes: Granite Gray



RSUB300

8" Passive Subwoofer
10" Reflective Woofer
Durable Composite Cabinet
Power Handling: 500W
Freq Response: 20Hz - 150Hz
Sensitivity: 90db
Finishes: Brown & Gray

OUTDOOR PATIO



OSD Audio Outdoor Patio Speakers serve up rich, dynamic sound at a fraction of the competition's price. Another typical improvement over the competition is enhanced bass response, especially in our 8" & 6.5" models. In addition to our 8" and 6.5" patio speakers, smaller 5.25" and 4" models, as well as single stereo and commercial 70v options make for a well-rounded line that spans a wide variety of sizes & features to fit nearly any application. All OSD Audio Patio Speakers come equipped with all-weather enclosures, brackets and grilles, so you will be enjoying high-quality sound for years to come. From large areas around a pool, to a small, focused patio, to commercial installs in restaurants and bars, OSD Audio has an All-Weather Patio Speaker for you!

KEY FEATURES



High Quality

- Durable UV resistant enclosures, sealed internal components, as well as weather-protected grilles and brackets
- 8", 6.5", 5.25" & 4" All-Weather speaker models adapt to any application
- Produce deep, rich bass and crystal clear high notes



70V Options

- Four commercial 70v models available in three speaker sizes
- Integrated 70v transformers with multiple tap settings
- Indoor/Outdoor design is ideal for a wide variety of commercial applications



Single Stereo Models

- Single stereo DVC (dual voice coil) speakers for stereo sound in a single speaker
- Both 6.5" and 5.25" single stereo models available
- Great for stereo sound when space is limited



AP850

8" Polypropylene Woofer
2" Supernil Soft Dome Tweeter
Durable UV Resistant, Sealed Enclosure
Commercial 70v Version Available (AP850-70V)
Powder Coated Brackets & Grilles
Power Handling: 200W
Freq Response: 30Hz - 22kHz
Sensitivity: 90db
Impedance: 8 ohms
Finishes: White & Black



AP840

8" Polypropylene Woofer
1" Supernil Soft Dome Tweeter
Durable UV Resistant, Sealed Enclosure
Powder Coated Brackets & Grilles
Power Handling: 200W
Freq Response: 37Hz - 22kHz
Sensitivity: 90db
Impedance: 8 ohms
Finishes: White & Black



AP670

6.5" Waterproof Paper Woofer
1" Silk Dome Tweeter
Durable UV Resistant, Sealed Enclosure
Powder Coated Brackets & Grilles
Power Handling: 120W
Freq Response: 44Hz - 22kHz
Sensitivity: 90db
Impedance: 8 ohms
Finishes: White & Black



AP650

6.5" Polypropylene Woofer
1" Silk Dome Tweeter
Durable UV Resistant, Sealed Enclosure
Commercial 70v Version Available (AP650-70V)
Powder Coated Brackets & Grilles
Power Handling: 150W
Freq Response: 37Hz - 22kHz
Sensitivity: 91db
Impedance: 8 ohms
Finishes: White & Black



AP640

6.5" Polypropylene Woofer
1" Supernil Soft Dome Tweeter
Durable UV Resistant, Sealed Enclosure
Commercial 70v Version Available (AP640T)
Powder Coated Brackets & Grilles
Power Handling: 150W
Freq Response: 39Hz - 20kHz
Sensitivity: 89db
Impedance: 8 ohms
Finishes: White & Black



AP650TT

6.5" Polypropylene Woofer
Dual 1" Tweeters
Single Stereo / Dual Voice Coil
Durable UV Resistant, Sealed Enclosure
Powder Coated Brackets & Grilles
Impedance: 8 / 16 ohms
Finishes: White & Black



AP550TT

5.25" Polypropylene Woofer
Dual 1" Tweeters
Single Stereo / Dual Voice Coil
Durable UV Resistant, Sealed Enclosure
Powder Coated Brackets & Grilles
Power Handling: 150W
Sensitivity: 90db
Finishes: White & Black



AP525

5.25" Polypropylene Woofer
1" Silk Dome Tweeter
Durable UV Resistant, Sealed Enclosure
Commercial 70v Version Available (AP525-70V)
Powder Coated Brackets & Grilles
Power Handling: 120W
Freq Response: 45Hz - 20kHz
Sensitivity: 90db
Impedance: 8 ohms
Finishes: White & Black



AP520

5.25" Polypropylene Woofer
1" Tweeter
Durable UV Resistant, Sealed Enclosure
Commercial 70v Version Available (AP520T)
Powder Coated Brackets & Grilles
Power Handling: 120W
Freq Response: 45Hz - 20kHz
Sensitivity: 88db
Impedance: 8 ohms
Finishes: White & Black



AP490

4" Waterproof Paper Woofer
1" Silk Dome Tweeter
Durable UV Resistant, Sealed Enclosure
Powder Coated Grilles
Power Handling: 100W
Freq Response: 60Hz - 22kHz
Sensitivity: 88db
Impedance: 8 ohms
Finishes: White & Black



AP450

4" Polypropylene Woofer
1/2" Tweeter
Durable UV Resistant, Sealed Enclosure
Powder Coated Brackets & Grilles
Power Handling: 110W
Freq Response: 59Hz - 22kHz
Sensitivity: 90db
Impedance: 8 ohms
Finishes: White & Black

OMNI & DECORATIVE OUTDOOR

OSD Audio Omni & In-Ground speakers are specifically designed to disperse sound evenly & discretely throughout a wide variety of outdoor applications. Sporting durable burial enclosures with omni directional 360 degree sound dispersion, these outdoor speakers are meant to integrate seamlessly into just about any landscape. The line includes two 8" options for large open areas, 5.25" and 3" solutions for smaller applications and an 8" passive subwoofer with integrated crossover that allows you to connect any of our outdoor speakers for use in a 2.1 configuration. Whether your outdoor project is big or small, the OSD Audio Omni & In-Ground speakers will deliver seamless, long-lasting sound.



KEY FEATURES



Landscape Ready

- Paintable green enclosures allow the omni speakers to easily adapt to nearly any landscape
- In-ground burial design makes it easy to conceal any number of speakers throughout the application



Great Coverage

- 360 degree omni directional dispersion pattern
- 8" models boast high power handling making them ideal for use in large open spaces



Weather Resistant

- Lasts for years, even in harsh conditions such as rain, sun, snow and extreme temperature fluctuations
- Durable cabinetry with sealed components and voice coils



OS850

8" Polypropylene Woofer
1" Polyamide Tweeter
360 Degree Sound Dispersion
Rugged Composite Cabinet
Power Handling: 300W
Freq Response: 38Hz - 20kHz
Sensitivity: 90db
Impedance: 8 ohms



OS790

8" Polypropylene Woofer
1" Polyamide Tweeter
360 Degree Sound Dispersion
UV & Impact Resistant ABS Enclosure
Power Handling: 200W
Freq Response: 40Hz - 20kHz
Sensitivity: 88db
Impedance: 8 ohms



OS525

5.25" Polypropylene Woofer
3/4" Polyamide Tweeter
360 Degree Sound Dispersion
UV & Impact Resistant ABS Enclosure
Power Handling: 100W
Freq Response: 50Hz - 20kHz
Sensitivity: 89db
Impedance: 8 ohms



OMSUB200

8" Passive Subwoofer
Integrated Crossover & Speaker
Outputs for 2.1 Configuration
UV & Impact Resistant ABS Enclosure
Power Handling: 250W
Freq Response: 50Hz - 250Hz (crossover at 250Hz)
Sensitivity: 88db
Impedance: 8 ohms



LS3

3" PE Cone
Pivoting 180 Degree Adjustability
Power Handling: 60W
Freq Response: 150Hz - 20kHz
Impedance: 8 ohms



PS520

5.25" Polypropylene Woofer
5/8" Polycarbonate Tweeter
Butyl Rubber Surround
UV & Impact Resistant ABS Enclosure
Integrated Water Drainage Tube
Power Handling: 100W
Freq Response: 60Hz - 20kHz
Sensitivity: 89db
Impedance: 8 ohms



PS525

5.25" Polypropylene Woofer
Dual 5/8" Polycarbonate Tweeters
Butyl Rubber Surround
Single Stereo / Dual Voice Coil
UV & Impact Resistant ABS Enclosure
Integrated Water Drainage Tube
Power Handling: 100W
Freq Response: 60Hz - 20kHz
Sensitivity: 89db
Impedance: 8 ohms



SP650

6.5" Polypropylene Woofer
Dual 2.5" Polyamide Tweeters
Butyl Rubber Surround
Single Stereo / Dual Voice Coil
Rugged Composite Cabinet
Power Handling: 150W
Freq Response: 75Hz - 22kHz
Sensitivity: 84db
Impedance: 8 ohms



FR525

5.25" Polypropylene Woofer
1/2" Polyamide Tweeter
Butyl Rubber Surround
Power Handling: 100W
Frequency Response: 60Hz - 20kHz
Sensitivity: 88db
Impedance: 8 ohms



AUDIO AMPLIFIERS

To perform at their best, speakers need clean power. Adding one or more high-quality amplifiers will go a long way in improving the performance of your system. OSD Audio offers a complete line of multi & 2-channels amps with various features and price points. Ideal for music systems, distributed audio, outdoor audio, or as a dedicated power amp for home theaters, our 2-channel line includes small table top units for powering a simple pair of speakers to high current amps such as our AMP300. This heavy-duty amplifier is perfect for use as a remote amp or as a single or dual zone amplifier and includes automatic dual source switching. The line also includes compact subwoofer amps with built-in crossover networks designed to be used with passive subwoofers.



KEY FEATURES



Multi Channel

- Powerful, durable, high current amplifiers
- Compact stereo, small application amps
- Multi-channel amplifiers perfect for whole house audio



Subwoofer Amps

- 150w and 40w models available to fit a variety of subwoofer sizes.
- Variable low pass crossover
- 4-8 ohm stable



Commercial Amps

- 70v, 100v & 8 ohm compatible
- Multiple mic & line level inputs with independent gain control
- Rack-mountable with integrated chime & paging features



MX1260

6-Zone / 12 Channel Stereo Multi-Channel Amplifier
40W RMS per Channel into 8 ohms
60W RMS per Channel into 4 ohms
80W RMS Bridged Mono into 8 ohms
Front Panel: Power & LED
Zone Indicators
Back Panel: RCA Audio Inputs, Auto Sensing, Master Level Zone Controls & Switchable 110/220 Voltage
4-8 Ohm Stable



AMP300

Stereo 2-Channel High Current Amplifier
150W RMS per Channel into 8 ohms
235W RMS per Channel into 4 ohms
475W RMS Bridged Mono into 8 ohms
Front Panel: Power, Volume, Balance Control, A/B
Speaker Switching & Voltage Meters
Back Panel: Dual Source RCA & Speaker Level Inputs, Auto Sensing / 12v Trigger, Master Level Control & Switchable 110/220 Voltage
2-8 Ohm Stable



AMP200

Stereo 2-Channel High Current Amplifier
80W RMS per Channel into 8 ohms
125W RMS per Channel into 4 ohms
200W RMS per Channel into 2 ohms
250W RMS Bridged Mono into 8 ohms
Front Panel: Power, Volume, Balance Control, A/B
Speaker Switching & Voltage Meters
Back Panel: Dual Source RCA & Speaker Level Inputs, Auto Sensing / 12v Trigger, Master Level Control & Switchable 110/220 Voltage
2-8 Ohm Stable



AMP120

Stereo 2-Channel Amplifier
50W RMS per Channel into 8 ohms
60W RMS per Channel into 4 ohms
160W RMS Bridged Mono into 8 ohms
Front Panel: Power, Volume, Balance Control & A/B
Speaker Switching
Back Panel: Dual Source RCA Inputs & Auto Sensing Switch
4-8 Ohm Stable



AMP60

Compact Stereo 2-Channel Amplifier
25W RMS per Channel into 8 ohms
Front Panel: Power, Volume Attenuation, Bass & Treble Control
Back Panel: RCA & 3.5mm Mini Stereo Inputs
8 Ohm Stable



MA2

Outdoor Stereo Amplifier/Receiver
Water-Resistant Design
25W RMS per Channel into 8 ohms
Front Panel: Power, Volume Attenuation & AM/FM Tuner Control
Back Panel: RCA & 3.5mm Mini Stereo Inputs
8 Ohm Stable



PA270

Mono 70v Commercial Amplifier
240W Total Output Power
Front Panel: Rack-Mountable, Power, Chime Feature, Aux In 1-3 Control, Mic In 1-3 Control, Bass & Treble Adjustment, Master Volume
Back Panel: 8 Ohm, 70v, 100v Speaker Connections, (3) RCA Aux inputs, (3) Mic Inputs & Switchable 110/220 Voltage Option



PA150

Mono 70v Commercial Amplifier
120W Total Output Power
Front Panel: Rack-Mountable, Power, Chime Feature, Aux In 1-3 Control, Mic In 1-3 Control, Bass & Treble Adjustment, Master Volume
Back Panel: 8 Ohm, 70v, 100v Speaker Connections, (3) RCA Aux inputs, (3) Mic Inputs & Switchable 110/220 Voltage Option



PA90

Mono 70v Commercial Amplifier
60W Total Output Power
Front Panel: Rack-Mountable, Power, Chime Feature, Aux In 1-3 Control, Mic In 1-3 Control, Bass & Treble Adjustment, Master Volume
Back Panel: 8 Ohm, 70v, 100v Speaker Connections, (3) RCA Aux inputs, (3) Mic Inputs & Switchable 110/220 Voltage Option



SMP250

Mono Subwoofer Amplifier
150W RMS / 250W Peak Total Output
Variable Low Pass Crossover: 35Hz - 180Hz
Front Panel: Power, Volume, Phase & Crossover Control, Voltage Meter
Back Panel: RCA, LFE & Speaker Level Inputs, Auto Sensing / 12v Trigger, Master Level Control & Switchable 110/220 Voltage Option
4-8 Ohm Stable



SMP60

40W RMS / 100W Peak Total Output
Variable Low Pass Crossover: 50Hz - 150Hz
Front Panel: Power, Volume & Crossover Control
Back Panel: RCA & 3.5mm Mini Stereo Inputs, Auto Sensing Switch
8 Ohm Stable

SPEAKER SELECTORS

OSD Audio's comprehensive line of Speaker Selectors allows you to gain complete control over your multi-zone audio system. With features like independent speaker and volume adjustability, dual input a/b source control, and impedance protection circuitry, you can easily custom tailor the sound in your particular application. A new and unique development in OSD's Speaker Selector lineup is the ATM-7 remote controlled speaker selector. The ATM-7 now allows you to remotely manipulate your speaker selector without having to be at the source. In addition to our tabletop speaker selectors, we also have in-wall distribution panels & a/b switches to choose from. OSD Audio's speaker selector line is yet another example that for every problem, OSD has the perfect solution.



KEY FEATURES



Customized Audio

- Distributes an amplified stereo audio signal into multiple zones
- Gain independent control of up to 12 pairs of speakers
- Includes impedance-protection circuitry



Flexible Options

- Add multiple pairs of speakers to your receiver or amplifier
- Listen to any combination of pairs simultaneously
- Solid-state circuit breakers protect from overload



Convenient Design

- Fits neatly into shelves or equipment racks
- Removable connecting blocks make wiring a breeze
- Easy installation with no additional power requirements



DSM8

8-Zone Speaker Selector
Dual Source Inputs
A/B Source Control per Zone
On/Off Zone Control
Impedance Protection Circuit



DSM6

6-Zone Speaker Selector
Dual Source Inputs
A/B Source Control per Zone
On/Off Zone Control
Impedance Protection Circuit



DSM4

4-Zone Dual Source Speaker Selector
Dual Source Inputs
A/B Source Control per Zone
On/Off Zone Control
Impedance Protection Circuit



ISS8

8-Zone Speaker Selector
On/Off Zone Control
Impedance Protection Circuit



ISS6

6-Zone Speaker Selector
On/Off Zone Control
Impedance Protection Circuit



ISS4

4-Zone Speaker Selector
On/Off Zone Control
Impedance Protection Circuit



ATM-7

7-Zone Speaker Selector
Dual Source Inputs
Remote A/B Source Control
Remote On/Off Zone Control



TSM12

12-Zone Speaker Selector
Dual Source Inputs
A/B Source Control
On/Off Zone Control
Autoformer Impedance Matching



TSM8

8-Zone Speaker Selector
Dual Source Inputs
A/B Source Control
On/Off Zone Control
Autoformer Impedance Matching



SSVC6D

Modified Single Source Speaker Selector
Connects 6 pairs of speakers
Solid state circuit breakers
Built-in overload protection
Impedance protection
Dual Source
Individual speaker volume control
Supports amplifiers up to 300W
Freq Response: 20Hz-20kHz



SSVC4

Four-zone output
Dual Zone output
Impedance matching volume control for each zone output
Dual source with independent a/b switch per zone
Freq Response: 20Hz - 20kHz
Removable connectors



SSVC2

Two-zone output
Dual Zone output
Impedance matching volume control for each zone output
Dual source with independent a/b switch per zone
Freq Response: 20Hz-20kHz
Removable connectors



SPW8

8-Zone In-Wall Distribution Panel
Power Handling: 150W



AB1.2

In-Wall A/B Switch
Power Handling: 100W

VOLUME CONTROLS

Volume Controls are a must for any multi-zone music system and OSD Audio's line of indoor and outdoor volume controls makes it easy to find the perfect model for your application. OSD Audio's vast line of indoor volume controls includes in-wall impedance matching and resistor-based models which are available in both round knob and slider options. We even offer a table-top style indoor volume control, as well as an in-wall commercial 70v model. Our volume control line is made complete by a variety of outdoor offerings. Our outdoor volume controls are available in both impedance matching and resistor-based designs, with multiple power handling settings to choose from. All OSD outdoor volume controls have a sealed, all-weather enclosure to protect them from the elements. With OSD Audio volume controls, you'll enjoy great sound throughout your home, indoors and outside, without having to run from room to room to turn the volume up or down.



KEY FEATURES



Indoor VC

- On/Off or A/B Switch Models
- Impedance matching & resistor-based models available
- Easy to install, single-gang mounting



Outdoor VC

- All-weather sealed enclosure
- Impedance matching & resistor-based models available
- Easily installs to conduit & wire runs



Commercial 70v VC

- Mono 70v/100v compatible
- White & Ivory in-wall models
- Easy to install, single-gang mounting



SVC300

In-Wall Volume Control
Impedance Matching
Power Handling: 300W
12-Step Attenuation
Removable Phoenix Connectors
Single Gang Box Fitment
Finishes: White, Ivory, Almond, Black, Brown



SVC100

In-Wall Volume Control
Impedance Matching
Power Handling: 100W
12-Step Attenuation
Removable Phoenix Connectors
Single Gang Box Fitment
Finishes: White, Ivory, Almond, Black, Brown



SVC405

In-Wall Volume Control with A/B Switch
Impedance Matching
Power Handling: 300W
12-Step Attenuation
Removable Phoenix Connectors
Single Gang Box Fitment
Finishes: White, Ivory, Almond



SVC205

In-Wall Volume Control with On/Off Switch
Impedance Matching
Power Handling: 300W
12-Step Attenuation
Removable Phoenix Connectors
Single Gang Box Fitment
Finishes: White, Ivory, Almond



VMS300

In-Wall Slider Volume Control
Impedance Matching
Power Handling: 300W
12-Step Slide Attenuation
Removable Phoenix Connectors
Single Gang Box Fitment
Finishes: White, Ivory, Almond, Black, Brown



VMS100

In-Wall Slider Volume Control
Impedance Matching
Power Handling: 100W
12-Step Slide Attenuation
Removable Phoenix Connectors
Single Gang Box Fitment
Finishes: White, Ivory, Almond, Black, Brown



VKR120

In-Wall Volume Control
Resistor-Based Design
Power Handling: 150W
11-Step Attenuation (Break Before Make)
Removable Phoenix Connectors
Single Gang Box Fitment
Finishes: White, Ivory, Almond



MONO70V

In-Wall Volume Control
Mono 70v/100v Compatible
Power Handling: 10W
Multi-Step Attenuation
Removable Phoenix Connector
Single Gang Box Fitment
Finishes: White & Ivory



OVC300

Outdoor Volume Control
Easy-Access Impedance Matching Switch
Sealed, Waterproof Enclosure
Power Handling: 300W
12-Step Attenuation
Labeled Terminal Leads
Finishes: Gray & White



OVC100

Outdoor Volume Control
Easy-Access Impedance Matching Switch
Sealed, Waterproof Enclosure
Power Handling: 100W
12-Step Attenuation
Labeled Terminal Leads
Finishes: Gray & White



OVC50

Outdoor Volume Control
Easy-Access Impedance Matching Switch
Sealed, Waterproof Enclosure
Power Handling: 50W
12-Step Attenuation
Labeled Terminal Leads
Finishes: Gray



OVC305R

Outdoor Volume Control
Resistor Based Design
Sealed, Waterproof Enclosure
Power Handling: 300W
11-Step Attenuation (Break Before Make)
Labeled Terminal Leads
Finishes: Gray & White





FIXED & TILT TV MOUNTS

OSD Audio's Fixed and Tilt TV Mounts are an easy, yet secure way to mount your flat panel LCD, LED or Plasma TV. Fixed flat models boast a low profile design that makes for an ultra-clean look when the TV is mounted and support a wide variety of screen sizes, VESA patterns & weights. OSD Audio tilt mounts offer the same great look and security of the fixed models, but allow you the option to tilt the display downward up to 10 degrees to accommodate your viewing location. Tilt mounts also include an integrated bubble level for the utmost convenience. If you're looking for a rugged, secure mount that doesn't break the bank, then OSD Audio has the fixed or tilt mount for you.



KEY FEATURES



Fixed Mounts

- Sturdy fixed, flat mounts accommodate screen sizes 23" - 63"
- Slim, low profile design for a seamless aesthetic
- Easy to install



Tilt Mounts

- Convenient & secure tilt mounts accommodate screen sizes 23" - 63"
- Tilt feature allows you to set screen straight or tilt downward up to 10 degrees
- Include integrated bubble levels



FM-48F

Ultra-thin Fixed Flat Mount
Screen Size: 37" - 63"
Max VESA: 800x400
Max Weight: 99 lbs
RoHS Compliant



FM-46F

Ultra-thin Fixed Flat Mount
Screen Size: 32" - 60"
Max VESA: 600x400
Max Weight: 99 lbs
RoHS Compliant



FM-44F

Ultra-thin Fixed Flat Mount
Screen Size: 23" - 42"
Max VESA: 400x400
Max Weight: 99 lbs
RoHS Compliant



FM-648

Fixed Flat Mount
Screen Size: 32" - 63"
Max VESA: 800x400
Max Weight: 143 lbs
RoHS Compliant



FM-644

Fixed Flat Mount
Screen Size: 32" - 42"
Max VESA: 400x400
Max Weight: 121 lbs
RoHS Compliant



FM-624

Fixed Flat Mount
Screen Size: 23" - 37"
Max VESA: 400x200
Max Weight: 99 lbs
RoHS Compliant



FM-148

Fixed Flat Mount
Integrated Bubble Level
Screen Size: 37" - 63"
Max VESA: 800x400
Max Weight: 165 lbs
RoHS Compliant



FM-144

Fixed Flat Mount
Integrated Bubble Level
Screen Size: 26" - 47"
Max VESA: 400x400
Max Weight: 165 lbs
RoHS Compliant



FM-01

Picture Frame Mount
Screen Size: 32" - 55"
Max VESA: 400x400
Max Weight: 110 lbs
RoHS Compliant



TM-148

Tilt Mount w/ Integrated
Bubble Level
Tilt: 0 -10 Degrees
Screen Size: 37" - 63"
Max VESA: 800x400
Max Weight: 165 lbs
RoHS Compliant



TM-144

Tilt Mount w/ Integrated
Bubble Level
Tilt: 0 -10 Degrees
Screen Size: 26" - 47"
Max VESA: 400x400
Max Weight: 165 lbs
RoHS Compliant



TM-43

Tilt Mount w/ Integrated
Bubble Level
Tilt: 0 -10 Degrees
Screen Size: 37" - 63"
Max VESA: 800x400
Max Weight: 165 lbs
RoHS Compliant



TM-43S

Tilt Mount w/ Integrated
Bubble Level
Tilt: 0 -10 Degrees
Screen Size: 32" - 60"
Max VESA: 615x410
Max Weight: 165 lbs
RoHS Compliant



TM-42

Tilt Mount w/ Integrated
Bubble Level
Tilt: 0 -10 Degrees
Screen Size: 23" - 37"
Max VESA: 420x230
Max Weight: 165 lbs
RoHS Compliant

FULL MOTION TV MOUNTS

OSD Audio's Full Motion TV Mounts offer high-end features and maximum flexibility at a great price point. OSD Audio's full motion mounts come fully equipped with adjustable tilt, swivel and screen rotation. This allows you to manipulate the placement of your TV just about any way you can think of. High weight handling and a wide variety of compatible VESA patterns makes for easy fitment and ultra-secure mounting. From drop-down displays, to corner applications, to large display solutions, OSD Audio has the perfect full motion mount for you.




KEY FEATURES



Full Motion

- Tilt adjustability up to +/- 70 degrees
- Swivel adjustability up to +/- 90 degrees
- Rotation & level adjustment up to 360 degrees



Easy Fitment

- Supports screen sizes from 10" - 63"
- Universal mounting is compatible with a wide variety of VESA patterns
- Corner friendly models available



Secure Mounting

- Sturdy, high-quality construction
- High max weight limits accommodate even the largest displays
- All mounting hardware, tools & instructions included



TSM-484

Tilt/Swivel Full Motion Mount
Screen Size: 37" - 63"
Tilt: +/- 15 Degrees
Swivel: +/- 60 Degrees
Level Adjustment: +/- 5 Degrees
Max VESA: 800x400
Max Weight: 132 lbs
RoHS Compliant



TSM-444

Tilt/Swivel Full Motion Mount
Screen Size: 23" - 42"
Tilt: +/- 15 Degrees
Swivel: +/- 60 Degrees
Level Adjustment: +/- 5 Degrees
Max VESA: 400x400
Max Weight: 99 lbs
RoHS Compliant



TSM-19-444

Full Motion Mount w/ Quad Arm
Screen Size: 26" - 47"
Tilt: +/- 15 Degrees
Swivel: +/- 60 Degrees
Level Adjustment: +/- 3 Degrees
Max VESA: 400x400
Max Weight: 99 lbs
RoHS Compliant



TSM-19-442

Full Motion Mount w/ Dual Arm
Screen Size: 26" - 47"
Tilt: +/- 15 Degrees
Swivel: +/- 90 Degrees
Level Adjustment: +/- 3 Degrees
Max VESA: 400x200
Max Weight: 66 lbs
RoHS Compliant



TSM-19-242

Full Motion TV Mount
Screen Size: 23" - 42"
Tilt: +/- 15 Degrees
Swivel: +/- 90 Degrees
Level Adjustment: +/- 3 Degrees
Max VESA: 400x200
Max Weight: 66 lbs
RoHS Compliant



TSM-19-241

Full Motion TV Mount
Screen Size: 23" - 42"
Tilt: +/- 15 Degrees
Swivel: +/- 90 Degrees
Level Adjustment: +/- 3 Degrees
Max VESA: 400x200
Max Weight: 66 lbs
RoHS Compliant



TSM-142A

Tilt/Swivel Full Motion TV Mount
Screen Size: 17" - 37"
Tilt: +/- 15 Degrees
Swivel: +/- 90 Degrees
Rotation: 360 Degrees
Max VESA: 200x200
Max Weight: 88 lbs
RoHS Compliant



TSM-141A

Tilt/Swivel Full Motion TV Mount
Screen Size: 17" - 37"
Tilt: +/- 15 Degrees
Swivel: +/- 90 Degrees
Rotation: 360 Degrees
Max VESA: 200x200
Max Weight: 88 lbs
RoHS Compliant



TSM-601M

Tilt/Swivel Full Motion TV Mount
Screen Size: 17" - 37"
Tilt: +/- 15 Degrees
Swivel: +/- 15 Degrees
Level Adjustment: +/- 5 Degrees
Max VESA: 200x200
Max Weight: 66 lbs
RoHS Compliant



TSM-02-223

Tilt/Swivel Full Motion TV Mount
Screen Size: 10" - 37"
Tilt: +/- 20 Degrees
Swivel: +/- 90 Degrees
Level Adjustment: 360 Degrees
Max VESA: 200x200
Max Weight: 66 lbs
RoHS Compliant



TSM-01-223

Tilt/Swivel Full Motion TV Mount
Screen Size: 13" - 23"
Tilt: +/- 15 Degrees
Swivel: +/- 90 Degrees
Level Adjustment: 360 Degrees
Max VESA: 100x100
Max Weight: 33 lbs
RoHS Compliant



TSM-101

Tilt/Swivel Full Motion TV Mount
Screen Size: 13" - 23"
Tilt: +/- 70 Degrees
Swivel: +/- 90 Degrees
Max VESA: 400x400
Max Weight: 33 lbs
RoHS Compliant



TSM-143

Tilt/Swivel Full Motion TV Mount
Screen Size: 13" - 23"
Tilt: +/- 15 Degrees
Swivel: +/- 60 Degrees
Rotation: 360 Degrees
Max VESA: 75x100
Max Weight: 33 lbs
RoHS Compliant



TSM-CM-222

Under Cabinet TV Mount
Screen Size: 17" - 37"
Tilt: -90 - 0 Degrees
Swivel: 360 Degrees
Max VESA: 200x200
Max Weight: 44 lbs
RoHS Compliant



TSM-CM-211

Under Cabinet TV Mount
Screen Size: 13" - 27"
Tilt: -90 - 0 Degrees
Swivel: 360 Degrees
Max VESA: 100x100
Max Weight: 44 lbs
RoHS Compliant



TSM-CM

Under Cabinet TV Mount
Screen Size: 13" - 23"
Tilt: -110 - 0 Degrees
Swivel: 360 Degrees
Max VESA: 100x100
Max Weight: 17 lbs
RoHS Compliant

DESKTOP, PROJECTOR & SHELF MOUNTS



OSD Audio's Desktop, Projector and Shelf Mounts are the perfect solution for your more custom mounting needs. It's not just your TV that OSD helps you to mount with premium function and security; we also offer desktop monitor, projector and component shelving solutions. Perfect for a professional or home office are our desktop monitor mounts which provide full motion tilt/swivel capabilities for up to four monitors at a time. A couple other great office mounts are the TSM-PRB-1 and TSM-PRB-2 projector mounts. The PRB's allow you to securely hang your project from the ceiling with our drop-down style design. The design also allows for tilt/swivel features for added adjustability. Rounding out the category are our single and double component shelf mounts. These elegant, yet functional mounts make for a great way to store many of the various devices being fed to your wall-mounted TV.



KEY FEATURES



Desktop Mounts

- Sturdy, secure desktop mounts accommodate 13"-23" monitors
- Multi-arm designs to support multiple monitors or extend reach & placement
- Tilt/swivel features offers full range of motion



Projector Mounts

- Ultra secure, ceiling drop-down style mounting
- Universal mounting pattern is compatible with a wide range of projectors
- Tilt/swivel features offers full range of motion



Shelf Mounts

- Single & double shelf models available to store multiple components
- Adjustable shelf positioning accommodates a range of different sized devices
- Strong, tempered glass shelf can support up to 22lbs



TSM-T13

Tilt & Swivel Desktop Monitor Mount
Double Arm Extended Reach
Monitor Size: 13" - 23"
Tilt: +/- 15 Degrees
Swivel: +/- 90 Degrees
Rotation: 360 Degrees
Max VESA: 100x100
Max Weight: 33 lbs



TSM-T12

Tilt & Swivel Desktop Monitor Mount
Monitor Size: 13" - 23"
Tilt: +/- 15 Degrees
Swivel: +/- 90 Degrees
Rotation: 360 Degrees
Max VESA: 100x100
Max Weight: 33 lbs



TSM-T9

Tilt & Swivel Desktop Dual Monitor Mount
Dual Monitors w/ Double Arm Extended Reach
Monitor Size: 13" - 23"
Tilt: +/- 60 Degrees
Swivel: +/- 90 Degrees
Rotation: 360 Degrees
Max VESA: 100x100
Max Weight: 33 lbs/ Monitor



TSM-02-C048

Tilt & Swivel Desktop Four Monitor Mount
Four Monitors w/ Double Arm Extended Reach
Monitor Size: 13" - 23"
Tilt: +/- 15 Degrees
Swivel: +/- 90 Degrees
Rotation: 360 Degrees
Max VESA: 100x100
Max Weight: 17 lbs



TSM-02-C024

Tilt & Swivel Desktop Dual Monitor Mount
Dual Monitors w/ Double Arm Extended Reach
Monitor Size: 13" - 23"
Tilt: +/- 15 Degrees
Swivel: +/- 90 Degrees
Rotation: 360 Degrees
Max VESA: 100x100
Max Weight: 17 lbs



TSM-02-C012

Tilt & Swivel Desktop Monitor Mount
Double Arm Extended Reach
Monitor Size: 13" - 23"
Tilt: +/- 15 Degrees
Swivel: +/- 90 Degrees
Rotation: 360 Degrees
Max VESA: 100x100
Max Weight: 17 lbs



TSM-02-C011

Tilt & Swivel Desktop Monitor Mount
Monitor Size: 13" - 23"
Tilt: +/- 15 Degrees
Swivel: +/- 90 Degrees
Rotation: 360 Degrees
Max VESA: 100x100
Max Weight: 17 lbs



TSM-PRB-2

Tilt & Swivel Projector Ceiling Mount
Tilt: +/- 15 Degrees
Swivel: 360 Degrees
Ceiling to Projector Extension: 16.92" - 25.59"
Universal Mounting Pattern
Max Weight: 44 lbs



TSM-PRB-1

Tilt & Swivel Projector Ceiling Mount
Tilt: +/- 15 Degrees
Swivel: 360 Degrees
Ceiling to Projector Extension: 3.14" or 6.69"
Universal Mounting Pattern
Max Weight: 22 lbs



DVD-SHELF-3B

Double Shelf Wall Mount
Shelf Material: 0.23"
Tempered Glass
Shelf Dimensions: 15.7" x 11.8"
Max Weight: 22 lbs



DVD-SHELF-2BE

Single Shelf Wall Mount
Shelf Material: 0.23"
Tempered Glass
Shelf Dimensions: 15.7" x 11.8"
Max Weight: 22 lbs



HDMI CABLES & COMPONENTS

High Definition Multimedia Interface (HDMI®) cables carry high definition signals of both audio and video in one, easy-to-connect cable. A digital version of analog component video cable, HDMI vastly simplifies the connection process and can have a great impact on picture and sound because it allows uncompressed signals and will not degrade. OSD Audio offers HDMI cables in three series: Premium, Value and Slim Locking. Our Premium and Value series are both high speed V1.4 - 4K cables. Both series are also shielded and CL3 rated for in-wall use and are available in a vast assortment of lengths as well as mini and micro connectors. The primary difference between the Premium and Value series is in the housing. While both utilize gold-plated connectors, the Premium series is a two-piece nickel-plated housing and the Value series is a molded plastic housing. The Slim Locking series is available in both the Premium and Value varieties but is designed with an ultra-slim shielded/CL3 rated jacket and tight-fit gold-plated connector that won't come loose from your device. The Slim Locking series is also high speed with Ethernet and audio return channel (ARC) and supports up to V1.4. To accompany our comprehensive line of HDMI cables, we have a variety of HDMI wall plates and splitters that make customizing your audio/video configuration simple, yet functional. OSD Audio's HDMI cables and components deliver a complete solution for all of your HD audio and video needs.



KEY FEATURES



Premium HDMI

- Premium high speed HDMI cable supports Ethernet V1.4
- Shielded & CL3 rated for in-wall use
- Nickel plated, metal housing with gold plated connectors



Slim Locking HDMI

- High speed HDMI cable with Ethernet & ARC supports V1.4
- Shielded & CL3 rated ultra-slim cable
- Premium metal & value molded plastic housing available with tight-fit gold plated connectors



Value HDMI

- High speed HDMI cable with Ethernet supports V1.4
- Shielded & CL3 rated for in-wall use
- Molded plastic housing (black or white) with gold plated connectors



HDMI Components

- 1 & 2 port HDMI single gang wall plates (supports V1.3)
- 2-way & 4-way HDMI Splitters distribute single HDMI in to multiple displays (supports V1.3)



PREMIUM HDMI

- 3FT Premium HDMI (P/N: HDMI-3ft-V14)
- 3FT Premium MINI HDMI (P/N: HDMI-Mini-3ft-V14)
- 6FT Premium HDMI (P/N: HDMI-6ft-V14)
- 9FT Premium HDMI (P/N: HDMI-9ft-V14)
- 12FT Premium HDMI (P/N: HDMI-12ft-V14)
- 15FT Premium HDMI (P/N: HDMI-15ft-V14)
- 20FT Premium HDMI (P/N: HDMI-20ft-V14)
- 25FT Premium HDMI (P/N: HDMI-25ft-V14)
- 30FT Premium HDMI (P/N: HDMI-30ft-V14)
- 40FT Premium HDMI (P/N: HDMI-40ft-V14)
- 50FT Premium HDMI (P/N: HDMI-50ft-V14)
- 60FT Premium HDMI (P/N: HDMI-60ft-V14)
- 75FT Premium HDMI (P/N: HDMI-75ft-V14)
- 100FT Premium HDMI (P/N: HDMI-100ft-V14)



SLIM LOCKING HDMI

- 20IN Premium Slim Locking HDMI (P/N: SL-HDAV-20IN-PL-V14)
- 3FT Premium Slim Locking HDMI (P/N: SL-HDAV-3FT-PL-V14)
- 6FT Premium Slim Locking HDMI (P/N: SL-HDAV-6FT-PL-V14)
- 9FT Premium Slim Locking HDMI (P/N: SL-HDAV-9FT-PL-V14)
- 12FT Premium Slim Locking HDMI (P/N: SL-HDAV-12FT-PL-V14)
- 15FT Premium Slim Locking HDMI (P/N: SL-HDAV-15FT-PL-V14)
- 20Inch Value Slim Locking HDMI (P/N: SL-HDAV-20IN-Val-V14)
- 3FT Value Slim Locking HDMI (P/N: SL-HDAV-3FT-Val-V14)
- 6FT Value Slim Locking HDMI (P/N: SL-HDAV-6FT-Val-V14)
- 9FT Value Slim Locking HDMI (P/N: SL-HDAV-9FT-Val-V14)
- 12FT Value Slim Locking HDMI (P/N: SL-HDAV-12FT-Val-V14)
- 15FT Value Slim Locking HDMI (P/N: SL-HDAV-15FT-Val-V14)



VALUE HDMI

- 3FT Value HDMI (P/N: HDMI-3ft-Value-V14)
- 3FT Value Mini HDMI (P/N: HDMI-Mini-3ft-Value-V14)
- 3FT Value MicroD HDMI (P/N: HDMI-MicroD-3ft-Value-V14)
- 3FT Value White HDMI (P/N: IN-HDMI-3FT-V14)
- 6FT Value HDMI (P/N: HDMI-6ft-Value-V14)
- 6FT Value MicroD HDMI (P/N: HDMI-MicroD-3ft-Value-V14)
- 6FT Value White HDMI (P/N: IN-HDMI-3FT-V14)
- 9FT Value HDMI (P/N: HDMI-9ft-Value-V14)
- 9FT Value MicroD HDMI (P/N: HDMI-MicroD-3ft-Value-V14)
- 12FT Value HDMI (P/N: HDMI-12ft-Value-V14)
- 12FT Value MicroD HDMI (P/N: HDMI-MicroD-3ft-Value-V14)
- 12FT Value White HDMI (P/N: IN-HDMI-3FT-V14)
- 15FT Value HDMI (P/N: HDMI-15ft-Value-V14)
- 20FT Value HDMI (P/N: HDMI-20ft-Value-V14)
- 25FT Value HDMI (P/N: HDMI-25ft-Value-V14)
- 30FT Value HDMI (P/N: HDMI-30ft-Value-V14)
- 40FT Value HDMI (P/N: HDMI-40ft-Value-V14)
- 50FT Value HDMI (P/N: HDMI-50ft-Value-V14)
- 60FT Value HDMI (P/N: HDMI-60ft-Value-V14)
- 75FT Value HDMI (P/N: HDMI-75ft-Value-V14)
- 100FT Value HDMI (P/N: HDMI-100ft-Value-V14)



HDMI SPLITTERS

- 1 In / 2 Out HDMI Splitter (P/N: HDMI-1x2-Splitter)
- 1 In / 4 Out HDMI Splitter (P/N: HDMI-1x4-Splitter)



HDMI WALLPLATES

- Single Port HDMI Wallplate (P/N: HDMI-1-PORT)
- Dual Port HDMI Wallplate (P/N: HDMI-2-PORT)

3.5MM MINI STEREO CABLES

OSD Audio 3.5mm Mini Stereo Cables make connecting smart phones, tablets and other audio devices a cinch. Whether you require a mini to mini aux cable, mini to RCA adapter cable or one of the many male/female adapter and extension combinations, OSD has you covered. These high-quality cables come in a variety of lengths and don't skimp where other cables might cut corners. All OSD Audio mini stereo cables are made up of oxygen free copper conductors, ultra-flexible shielded jackets and gold-plated connectors. OSD Audio's high build quality on these cables will guarantee that the weak link in your audio system won't be your aux cable.

KEY FEATURES



Mini - RCA

- 3.5mm mini stereo to RCA audio adapter cable
- Gold-plated connectors
- Shielded jacket



Mini - AUX

- 3.5mm male to male mini stereo aux cable
- Oxygen free copper conductors
- Ultra-flexible jacket



MINI - RCA

- 1FT (P/N: MS-1FT)
- 3FT (P/N: MS-3FT)
- 6FT (P/N: MS-6FT)
- 12FT (P/N: MS-12FT)



MINI - AUX

- 3FT (P/N: MS-AUX-3FT)
- 6FT (P/N: MS-AUX-6FT)
- 9FT (P/N: MS-AUX-9FT)
- 12FT (P/N: MS-AUX-12FT)



MINI EXTENSIONS

- 6FT (P/N: MS-EXT-6FT)
- 9FT (P/N: MS-EXT-9ft)

WALL PLATES & CABLE MANAGEMENT



Passing cables and wire through the wall can be a challenge to keep organized and clean. OSD Audio's Wall Plates were designed to solve that very problem. We offer both gold-plated binding post wall plates to organize speaker connections, as well as pass through bundle style plates to cleanly pass cables and wire through your wall. Both lines of wall plates come in single and double gang sizes and can be inserted into a multi-gang faceplate for a sleek, seamless look

KEY FEATURES



Connector Plates

- Easily connect & pass speaker wire runs through your wall while maintaining a clean look
- Gold-plated binding posts accept bare wire or banana plugs for quick disconnect
- Single & double gang plates that accommodate multiple speakers connections



Pass Through Plates

- Easily pass cables & wires through your wall while maintaining a clean look
- Single & double gang sizes available
- Multiple color finishes



WP20

20-Terminal 7.1 Home Theatre Wall Plate
18 Gold-Plated Binding Posts w/ 2 Gold-Plated RCA connections
Double Gang Fitment
Finishes: White



WP16

16-Terminal 7.1 Home Theatre Wall Plate
14 Gold-Plated Binding Posts w/ 2 Gold-Plated RCA connections
Double Gang Fitment
Finishes: White



WP12

6-Speaker Binding Post Wall Plate
12 Gold-Plated Binding Posts
Double Gang Fitment
Finishes: White



WP8

4-Speaker Binding Post Wall Plate
8 Gold-Plated Binding Posts
Single Gang Fitment
Finishes: White



WP4

2-Speaker Binding Post Wall Plate
4 Gold-Plated Binding Posts
Single Gang Fitment
Finishes: White



WP2

Single Speaker Binding Post Wall Plate
2 Gold-Plated Binding Posts
Single Gang Fitment
Finishes: White



PTW-01-2

Double Gang Pass Through Bundle Cable Wall Plate
2" Pass Through Diameter
Finishes: White



PTW-01-1

Single Gang Pass Through Bundle Cable Wall Plate
1" Pass Through Diameter
Finishes: White



PTW-DOUBLE

Double Gang Pass Through Bundle Cable Wall Plate
2" Pass Through Diameter
Finishes: White, Ivory & Black



PTW-SINGLE

Single Gang Pass Through Bundle Cable Wall Plate
1" Pass Through Diameter
Finishes: White, Ivory & Black



INV-DOUBLE

Double Gang Inverted Pass Through Bundle Cable Wall Plate
2" Pass Through Diameter
Finishes: White, Ivory & Black



INV-SINGLE

Single Gang Inverted Pass Through Bundle Cable Wall Plate
1" Pass Through Diameter
Finishes: White, Ivory & Black

INSTALL BRACKETS & BACK BOXES

To accommodate all of your new construction speaker installation needs, OSD Audio offers a variety of in-ceiling and in-wall speaker brackets and back boxes. OSD Audio's speaker brackets are made up of a durable plastic ring that secures to the studs in your walls by way of two aluminum wings. The in-ceiling and in-wall speaker brackets make the drywall framing process much easier even include a clip to hold your speaker wire. In addition to brackets, we also offer in-ceiling speaker back boxes for our 6.5" and 8" models. OSD Audio speaker back boxes help to reduce sound bleed, improve bass response and keep insulation off the back of the speaker. Not every job is a retrofit. That's why OSD Audio has you covered from start to finish.



KEY FEATURES



Construction Brackets

- New construction in-ceiling & in-wall speaker brackets
- Fits OSD Audio 5.25", 6.5" & 8" in-ceiling & in-wall models
- Makes new construction installation simple



Back Boxes

- New construction in-ceiling speaker back boxes
- Fits OSD Audio 10 In-wall Subwoofers
- Eliminates bleed, improves bass response & protects speaker from insulation



NCCB8

New Construction In-Ceiling Speaker Bracket
Cutout Diameter: 9 1/2"



NCCB6

New Construction In-Ceiling Speaker Bracket
Cutout Diameter: 7 3/4"



NCCB5

New Construction In-Ceiling Speaker Bracket
Cutout Diameter: 6 3/4"



NCCB8-K

New Construction In-Ceiling Speaker Bracket
Cutout Diameter: 9 7/8"



NCCB6-K

New Construction In-Ceiling Speaker Bracket
Cutout Diameter: 8 1/4"



NCB18

New Construction In-Wall Speaker Bracket
Cutout Diameter: 12 3/4" x 7 3/4"



NCB16

New Construction In-Wall Speaker Bracket
Cutout Diameter: 10 3/4" x 7 1/2"



BBIWS10

New Construction In-Wall IWS10 In-wall Passive Sub Back-box
Fire-retardant Metal Construction w/ Soundproofed Interior

Symbols

3.5mm Mini Stereo Cables 58

70V COMMERCIAL 14–15

C1070V 15

C1090VK 15

ICE620ST 15

ICE800ST 15

ICE840ST 15

ICE840TT 9

PC540 25

PC640 25

70V Transformer 14

A

ACCESSORIES

Back Boxes 62

Connector Plates 60

IWS10 Sub Back-box 63

New Construction In-Ceiling 63

New Construction In-Wall 63

Pass Through Plates 60

Wall Plates 60

ACE400 11

ACE500 11

ACE590 11

All-Weather 34

Amplifiers 39

Commercial Amps 40

Multi Channel 40

Subwoofer Amps 40

B

BACK BOXES 62

IWS10 Passive Sub Back-box 63

BLUETOOTH SPEAKERS

BTF-525 31

BTP-650 31

BTR-150 31

BTR-800 31

BTR-800TT 31

SP2.1 25

SS2.1 25

C

CABLES 56

3.5mm Mini Stereo 58

Mini - AUX 58

Mini - RCA 58

Premium HDMI 56

CABLES & ACCESSORIES 55–61

Back Boxes 62

Connector Plates 60

HDMI Wallplate 57

Slim Locking HDMI 56

Value HDMI 56

Wall Plates 60

Commercial 70v VC 44

COMMERCIAL APPLICATIONS 14

C1070V 15

C1090VK 15

ICE620ST 15

ICE800ST 15

ICE840ST 15

PC540 25

PC640 25

Connector Plates 60

Construction Brackets 62

New Construction In-Ceiling 63

New Construction In-Wall 63

CUSTOM SERIES 10 22

CW-540SQ 21

CW-640SQ 21

CW-840SQ 21

D

Desktop Monitor Mounts 52

Desktop Mounts 52

Down-Firing 26

Dual Zone Amplifier 40

E

ELECTRONICS 39

Speaker Selectors 42

Volume Controls 44

F

Fixed TV Mounts 48

Frog Speaker 37

Front-Firing 26

Full Motion TV Mounts 50

H

HDMI Cables 56

HDMI Components 56

HDMI Splitter 57

HDMI Wallplate 57

High Definition Multimedia Interface 56

I

IN-CEILING SPEAKERS 6–15

ICE530 11

ICE540 9

ICE600TTWRS 13

ICE600WRS 13

ICE610 11

ICE620 11

ICE620TT 11

ICE640 9

ICE640TT 9

ICE660 9

ICE800 11

ICE800TTWRS 13

ICE800WRS 13

ICE810 11

ICE840 9

Indoor VC 44

In-Ground Speakers 36

INSTALL BRACKETS 62

IN-WALL 17

CUSTOM SERIES 22

CW-540SQ 21

CW-640SQ 21

CW-840SQ 21

IW520 23

IW530 23

IW540 21

IW545 LCR 21

IW680 21

IW800 23

IW810 23

IW840 21

MK-IW550 LCR 19

MK SERIES 18

MK-W650 19

MK-W850 19

Passive In-Wall Subwoofer 27

PRO SERIES 20

In-Wall Subwoofer 26

IWS-8W 27

IWS-10 27

IWS-88 27

Passive In-Wall Subwoofer 27

L

Landscape Speaker 37

LCR SPEAKERS 19

IW545 LCR 21

MK-IW550 LCR 19

M

Mini - AUX 58

Mini - RCA 58

MK SERIES 6–7 See also IN-WALL

Moisture-Resistant Speakers 12–13

MULTIMEDIA SPEAKERS 24

PC540 25

PC640 25

PC690 25

PC850 25

Pendant Series 24

Sound Platform 24

SoundSole 25

SP2.1 25

SPHERE1 25

Sphere Speaker 24

SS2.1 25

N

New Construction In-Ceiling 63

New Construction In-Wall 63

O

OMNI & DECORATIVE 36

Frog Speaker 37

In-Ground Speakers 36

Planter Speaker 37

Omni Directional 36

OUTDOOR 29

All-Weather 34

Commercial 70v 35

Dual Tweeter 35

Landscape Speaker 37

OMNI & DECORATIVE 36

Omni Rock Speaker 32

Passive Rock Subwoofer 33

Patio Speakers 34

Rock Speakers 32

Weather Resistant 36

Wireless Outdoor Speakers 30

Outdoor VC 44

P

Passive In-Wall Subwoofer 27

IWS-8W 27

IWS-10 27

IWS-88 27

Pass Through Plates 60

Patio Speakers 34

Pendant Series 24

Planter Speaker 37

Powered Subwoofer 27

P8 27

PS10 27

PS12 27

PS88 27

S-10 27

Projector Mounts 52

PRO SERIES 8 20

R

Rock Speakers 32

S

Shelf Mounts 52

Sound Bar

SP2.1 25

SS2.1 25

Sound Platform 24

SoundSole 25

Speaker Selectors 42

SPHERE1 25

Sphere Speaker 24

SUBWOOFERS 26 27

Down-Firing 26

Front-Firing 26

IWS-8W 27

IWS-88 27

P8 27

Passive In-Wall Subwoofer 27

PS10 27

PS12 27

PS88 27

S-10 27

S-12 27

T

Tilt TV Mounts 48

Trimless Thin Bezel 6–7 10–11

TV MOUNTS 47

Desktop Monitor Mounts 52

Fixed TV Mounts 48

Full Motion TV Mounts 50

Projector Mounts 52

Shelf Mounts 52

Tilt TV Mounts 48

V

Value HDMI 56

Volume Controls 44

Commercial 70v VC 44

Indoor VC 44

Outdoor VC 44

W

Wall Plates 60

Weather Resistant 36

Whole House Audio 22

WIRELESS OUTDOOR 30



775 Columbia Street Brea, CA 92821 | 888.779.4968 | osdaudio.com