

TELEDEX



Opal RediDock

Opal DCT Cordless

OPAL DCT 1900/2900/1800/2800 SERIES

1.8 GHz and 1.9 GHz cordless phone that supports multiple RediDock™ Handsets within the room.

A Cetus, Inc. brand.

- **1.9 and 1.8 GHz DECT Technology** for best range, clarity & security
- **Single or Two line configuration**
- **SIP based protocol**
- **EZ-Answer** connects to incoming call by pressing any key
- **Superior Quality Speakerphone** for convenient Hands-free calls
- **Two lines with conference***
- **PrimeLine/RingLine Select™** automatically chooses the correct available line
- **AutoSync** – handset automatically syncs with base unit when in cradle
- **ExpressNet™** broadband-ready
- **Easy-access data port**
- **Up to ten programmable guest service buttons**
- **LifeLinePlus** allows use during power failure
- **Last number redial**
- **Lighted handset keypad**
- **Handset page/locator**
- **Low battery indicator**
- **Breakage-resistant, non-extending antenna**
- **Large printable faceplate area**
- **Line status indicators***



- **Bright message wait lamp and positive charge indicator**
- **morePhone™ Overage Program** with each qualifying shipment of TeledeX telephones includes extra sets at no charge.
- **5-Year Warranty**

**Two-line models only*

OPAL DCT 1900/2900/1800/2800 SERIES

SPECIFICATIONS

Standard Colour: Ash and Black
Footprint: 6.0" x 9.0" (15.24cm x 22.86cm)
Footprint (RediDock): 2.75" x 8.17" (7.0cm x 20.08cm)
Weight: 2.0 lbs. (0.9kg)
Weight (Redidock) 7 oz. (0.2kg) (without handset)
 12 oz. (0.34kg) (with handset)
Frequency: 1.9 GHz or 1.8 GHz
Power: 9 VDC adapter
Standby time: 14 days

Talk time: 4 hours
Humidity:65% ± 20%
Temperature:77°F ± 50° (25°C ± 10°C)
Packaging: 12 per carton
Packaging (RediDock): 20 per carton
Faceplate Size: Full length
FCC Specifications: Meet or exceeds
 Part 15, Subpart J,
 Class A, Part 68

Safety Standard: ETL and CE
Operating Voltage: 24 to 56 VDC Non-Polarity
Flash Timing: 600 ms
Ringer Equivalence: Z (Use only behind PBX)
Handset: Hearing Aid compatible
Line Cord: 15-foot, 2 RJ45

Part Numbers

DECT 1.9 GHz (Single line)

Opal DCT1905

OPL95149 Ash
 OPL951491 Black

Opal DCT1910

OPL95339 Ash
 OPL953391 Black

RediDock

RD1910 (Single-line)

OPL95339HDKIT Ash
 OPL953391HDKIT Black

DECT 1.9 GHz (Two line)

Opal DCT2905

OPL97149 Ash
 OPL971491 Black

Opal DCT2910

OPL97359 Ash
 OPL973591 Black

RediDock

RD2910 (Two-line)

OPL97359HDKIT Ash
 OPL973591HDKIT Black

DECT 1.8 GHz (Single line)

Opal DCT1805

OPL95148 Ash
 OPL951481 Black

Opal DCT1810

OPL95338 Ash
 OPL953381 Black

RediDock

RD1910 (Single-line)

OPL95338HDKIT Ash
 OPL953381HDKIT Black

DECT 1.8 GHz (Single line)

Opal DCT2805

OPL97148 Ash
 OPL971481 Black

Opal DCT2810

OPL97358 Ash
 OPL973581 Black

RediDock

RD2810 (Single-line)

OPL97358HDKIT Ash
 OPL973581HDKIT Black



Continuing the tradition.

To learn more, or to place an order, please visit www.TeledeX.com, call +1 719 638 8821 or email sales@teledeX.com.