

**TELEDEX**



# SIP ND2100/2200 SERIES CORDED

The first IP phone designed just for hotels.

**iPhone** TELEDEX

Full-featured. Rock solid.

A Cetus, Inc. brand.



# THE POWER AND FLEXIBILITY OF SIP, MADE JUST FOR HOSPITALITY.



**Teledex iPhone SIP ND2200 series phones are the perfect complement to our large color display iPhones.** Designed for the specific needs of the global hospitality industry, Teledex iPhones are easy for IT managers to set up, and easy for your guests to use. You get the outstanding voice quality and durability that Teledex is known for. And because these VoIP phones share the same attractive case design as our analog iPhones, you can install a mix of technologies (SIP and analog) in a single deployment and still present a consistent look and feel.

- Single or Two line configuration
- SIP based protocol
- Codecs Supported: G711a; G711µ; G729
- Supports 802.1Q VLAN tagging
- 2-port 10/100 Ethernet switch
- Speakerphone
- Up to 10 programmable service keys
- Hold, Mute, Conference\*, Redial keys
- Conference
- ADA-compliant volume control with enhanced Sonica™ hearing aid compatibility
- Visual message waiting indicator
- morePhone™ SM Overage Program with each qualifying shipment of Teledex telephones includes extra sets at no charge.
- 5-Year Warranty

*\*Two-line models only*

*Visit [www.teledex.com](http://www.teledex.com) for the latest VOIP switch certifications.*

## SIP ND2100/2200 SERIES CORDED

### SPECIFICATIONS

<b>Standard Colour:</b> .....	Ash and Black	<b>Packaging:</b> .....	12 per carton	<b>Operating Voltage:</b> .....	24 to 56 VDC Non-Polarity
<b>Footprint:</b> .....	6.0" x 9.0" (15.2cm x 22.9cm)	<b>Faceplate Size:</b> .....	Full length	<b>Flash Timing:</b> .....	600 ms
<b>Weight:</b> .....	2.0 lbs. (0.9kg)	<b>FCC Specifications:</b> .....	Meet or exceeds Part 15, Subpart J, Class A, Part 68	<b>Ringer Equivalence:</b> .....	Z (Use only behind PBX)
<b>Power:</b> .....	Local or PoE (Optional)	<b>Safety Standard:</b> .....	ETL and CE	<b>Registered Connector:</b> .....	USOC RJ-14
<b>Humidity:</b> .....	65% ± 20%			<b>Handset:</b> .....	Hearing Aid compatible
<b>Temperature:</b> .....	77°F ± 50° (25°C ± 10°C)			<b>Cords &amp; Line:</b> .....	.15-foot RJ45/10-foot coil

### Part Numbers

#### Single-Line Models

##### ND2105s (5-button speaker)

IPN331491P ..... Ash

IPN331491IP ..... Black

##### ND2110s (10-button speaker)

IPN3333491P ..... Ash

IPN3333491IP ..... Black

#### Two-Line Models

##### ND2205s (5-button speaker)

IPN341491P ..... Ash

IPN341491IP ..... Black

##### ND2210s (10-button speaker)

IPN343591P ..... Ash

IPN343591IP ..... Black



**Continuing the tradition.**

To learn more, or to place an order, please visit [www.Teledex.com](http://www.Teledex.com), call +1 719 638 8821 or email [sales@teledex.com](mailto:sales@teledex.com).